NOTES: UNLESS OTHERWISE SPECIFIED
1. REMOVE ALL BURRS AND SHARP EDGES .030 R MAX.
   DO NOT CHAMFER EDGES OF THE HOLES
2. MACHINED SURFACE ROUGHNESS 125
3. MATERIAL – 8851.920D4–700
4. TEXT MARKINGS TO BE EITHER KROY LABELS OR ENGRAVED.
   APPROXIMATELY WHERE SHOWN
   KROY LABELS BLACK ON CLEAR 18 PT FOR LABELING
   ENGRAVE TEXT .01 DP ARIAL FONT .150 ht

REVISIONS						
ZONE	LTR	REVISIONS	ECR	DATE	BY	APRV
	--	INTIAL RELEASE		NOV05	PJS	PJS



ALTERED ITEM
NOAO 8851.920D4-700

QTY. REQ.	PART OR IDENTIFYING NO.	DESCRIPTION	MATERIAL/SPECIFICATION	IDENT.	ITEM NO.

TOLERANCES UNLESS OTHERWISE NOTED
.XX ±.03 .XXX ±.010 ANGULAR ±.5°
THIRD ANGLE PROJECTION

NATIONAL SOLAR OBSERVATORY
OPERATED BY THE
ASSOCIATION OF UNIVERSITIES FOR RESEARCH IN ASTRONOMY
UNDER COOPERATIVE AGREEMENT WITH
NATIONAL SCIENCE FOUNDATION

DO NOT SCALE DRAWING

NAME: DETAIL MODIFICATION POWER SUPPLY REAR PANEL

USED ON: MONSOON

REF:

NEXT ASSEMBLY: MNSN-EL-02-0007

DWG SIZE: D

REV: --

SCALE:	DESIGNED BY	DATE	CHECKED BY	DATE	DWG NO
FULL	D.DRYDEN	MAR05			MNSN-EL-02-1013
DWG PRODUCED USING	DRAWN BY	DATE	APPROVED BY	DATE	
AUTOCAD LT2000	D.STOVER	JUL06			
	PRINT ISSUED	DATE	APPROVED BY	DATE	RELEASED

SHEET 1 OF 1