

LogiCORE™ IP FIFO Generator v4.4

User Guide

UG175 September 19, 2008





Xilinx is disclosing this user guide, manual, release note, and/or specification (the "Documentation") to you solely for use in the development of designs to operate with Xilinx hardware devices. You may not reproduce, distribute, republish, download, display, post, or transmit the Documentation in any form or by any means including, but not limited to, electronic, mechanical, photocopying, recording, or otherwise, without the prior written consent of Xilinx. Xilinx expressly disclaims any liability arising out of your use of the Documentation. Xilinx reserves the right, at its sole discretion, to change the Documentation without notice at any time. Xilinx assumes no obligation to correct any errors contained in the Documentation, or to advise you of any corrections or updates. Xilinx expressly disclaims any liability in connection with technical support or assistance that may be provided to you in connection with the Information.

THE DOCUMENTATION IS DISCLOSED TO YOU "AS-IS" WITH NO WARRANTY OF ANY KIND. XILINX MAKES NO OTHER WARRANTIES, WHETHER EXPRESS, IMPLIED, OR STATUTORY, REGARDING THE DOCUMENTATION, INCLUDING ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT OF THIRD-PARTY RIGHTS. IN NO EVENT WILL XILINX BE LIABLE FOR ANY CONSEQUENTIAL, INDIRECT, EXEMPLARY, SPECIAL, OR INCIDENTAL DAMAGES, INCLUDING ANY LOSS OF DATA OR LOST PROFITS, ARISING FROM YOUR USE OF THE DOCUMENTATION.

© 2005–2008 Xilinx, Inc. All rights reserved.

XILINX, the Xilinx logo, the Brand Window, and other designated brands included herein are trademarks of Xilinx, Inc. All other trademarks are the property of their respective owners.

Revision History

The following table shows the revision history for this document.

Date	Version	Revision
04/28/05	1.1	Initial Xilinx release.
8/31/05	2.0	Updated guide for release v2.2, added SP3 to ISE v7.1i, incorporated edits from engineering specific for this release, including FWFT, and Built-in FIFO flags, etc.
1/11/06	3.0	Updated for v2.3 release, ISE v8.1i.
7/13/06	4.0	Added Virtex-5 support, reorganized Chapter 5, added ISE v8.2i, version to 3.1
9/21/06	5.0	Core version updated to v3.2; support added for Spartan-3A.
2/15/07	6.0	Core version updated to 3.3; Xilinx tools updated to 9.1i.
4/02/07	6.5	Added support for Spartan-3A DSP devices.
8/8/07	6.6	Updated core to v4.1, ISE tools 9.2i, Cadence IUS v5.8.
10/10/07	7.0	Updated core to v4.2, IUS to v6.1, Xilinx trademark references.
3/24/08	8.0	Updated core to v4.3, ISE tools 10.1, ModelSim v6.3c.
9/19/08	9.0	Updated core to v4.4, ISE tools 10.1, SP3.

Table of Contents

Preface: About This Guide

Guide Contents	11
Conventions	12
Typographical	12
Online Document	13

Chapter 1: Introduction

About the Core	15
Recommended Design Experience	15
Technical Support	16
Feedback	16
FIFO Generator	16
Document	16

Chapter 2: Core Overview

Feature Overview	17
Clock Implementation Operation	17
Virtex-5 FPGA Built-in FIFO Support	17
Virtex-4 FPGA Built-in FIFO Support	17
First-Word Fall-Through	17
Memory Types	18
Non-Symmetric Aspect Ratio	18
Embedded Registers in block RAM and FIFO Macros (Virtex-4 and Virtex-5 Devices)	18
Error Correction Checking	19
Core Configuration and Implementation	19
Common Clock: Block RAM, Distributed RAM, Shift Register	19
Common Clock: Virtex-5 or Virtex-4 FPGA Built-in FIFO	19
Independent Clocks: Block RAM and Distributed RAM	20
Independent Clocks: Built-in FIFO for Virtex-5 or Virtex-4 FPGAs	20
FIFO Generator Features	20
Using Block RAM FIFOs Instead of Built-in FIFOs	21
FIFO Interfaces	22
Interface Signals: FIFOs With Independent Clocks	22
Interface Signals: FIFOs with Common Clock	26

Chapter 3: Generating the Core

CORE Generator Graphical User Interface	31
FIFO Implementation	32
Component Name	32
FIFO Implementation	32
Common Clock (CLK), Block RAM	33
Common Clock (CLK), Distributed RAM	33

Common Clock (CLK), Shift Register	33
Common Clock (CLK), Built-in FIFO	33
Independent Clocks (RD_CLK, WR_CLK), Block RAM	33
Independent Clocks (RD_CLK, WR_CLK), Distributed RAM	33
Independent Clocks (RD_CLK, WR_CLK), Built-in FIFO	33
Performance Options and Data Port Parameters	34
Read Mode	34
Standard FIFO	34
First-Word Fall-Through FIFO	34
Built-in FIFO Options	35
Read/Write Clock Frequencies	35
Data Port Parameters	35
Write Width	35
Write Depth	35
Read Width	35
Read Depth	35
Implementation Options	35
Error Correction Checking	35
Use Embedded Registers in Block RAM or FIFO	35
Optional Flags, Handshaking, and Initialization	36
Optional Flags	36
Almost Full Flag	36
Almost Empty Flag	37
Handshaking Options	37
Write Port Handshaking	37
Read Port Handshaking	37
Initialization and Programmable Flags	38
Initialization	38
Reset Pin	38
Use Dout Reset	39
Programmable Flags	39
Programmable Full Type	39
Programmable Empty Type	39
Data Count	40
Data Count Options	40
Use Extra Logic For More Accurate Data Counts	40
Data Count (Synchronized With Clk)	40
Write Data Count (Synchronized with Write Clk)	41
Read Data Count (Synchronized with Read Clk)	41
Summary	41

Chapter 4: Designing with the Core

General Design Guidelines	43
Know the Degree of Difficulty	43
Understand Signal Pipelining and Synchronization	43
Synchronization Considerations	43
Initializing the FIFO Generator	44
FIFO Implementations	45
Independent Clocks: Block RAM and Distributed RAM	45
Independent Clocks: Built-in FIFO	46
Common Clock: Built-in FIFO	47

Common Clock FIFO: Block RAM and Distributed RAM	48
Common Clock FIFO: Shift Registers	48
FIFO Usage and Control	49
Write Operation	49
ALMOST_FULL and FULL Flags	49
Example Operation	50
Read Operation	50
ALMOST_EMPTY and EMPTY Flags	50
Modes of Read Operation	51
Handshaking Flags	53
Write Acknowledge	53
Valid	53
Example Operation	54
Underflow	55
Overflow	56
Example Operation	56
Programmable Flags	56
Programmable Full	57
Programmable Empty	59
Data Counts	61
Data Count (Common Clock FIFO Only)	62
Read Data Count (Independent Clock FIFO Only)	62
Write Data Count (Independent Clock FIFO Only)	62
First-Word Fall-Through Data Count	63
Example Operation	65
Non-symmetric Aspect Ratios	65
Non-symmetric Aspect Ratio and First-Word Fall-Through	68
Embedded Registers in block RAM and FIFO Macros (Virtex-4 and Virtex-5 FPGAs)	69
Standard FIFOs	69
Block RAM Based FWFT FIFOs	69
Built-in Based FWFT FIFOs (Common Clock Only)	69
Built-in Error Correction Checking	70
Reset Behavior	71
Asynchronous Reset	71
Synchronous Reset	75
Actual FIFO Depth	76
Block RAM, Distributed RAM and Shift RAM FIFOs	76
Virtex-5 FPGA Built-In FIFOs	77
Virtex-4 FPGA Built-In FIFOs	78
Latency	78
Non-Built-in FIFOs: Common Clock and Standard Read Mode Implementations	78
Non-Built-in FIFOs: Common Clock and FWFT Read Mode Implementations	79
Non-Built-in FIFOs: Independent Clock and Standard Read Mode Implementations	81
Non-Built-in FIFOs: Independent Clock and FWFT Read Mode Implementations	82
Virtex-5 FPGA Built-in FIFOs: Common Clock and Standard Read Mode Implementations	84
Virtex-5 FPGA Built-in FIFOs: Common Clock and FWFT Read Mode Implementations	85
Virtex-5 FPGA Built-in FIFOs: Independent Clocks and Standard Read Mode Implementations	86
Virtex-5 FPGA Built-in FIFOs: Independent Clocks and FWFT Read Mode Implementations	87

Chapter 5: Special Design Considerations

Resetting the FIFO	89
Continuous Clocks	89
Pessimistic Full and Empty	89
Programmable Full and Empty	90
Simultaneous Assertion of Full and Empty Flag	90
Write Data Count and Read Data Count	91
Setup and Hold Time Violations	91

Chapter 6: Simulating Your Design

Simulation Models	93
-------------------------	----

Appendix A: Performance Information

Resource Utilization and Performance	95
--	----

Appendix B: Core Parameters

FIFO Parameters	99
-----------------------	----

Schedule of Figures

Chapter 2: Core Overview

<i>Figure 2-1: FIFO with Independent Clocks: Interface Signals</i>	22
--	----

Chapter 3: Generating the Core

<i>Figure 3-1: Main FIFO Generator Screen</i>	32
<i>Figure 3-2: Performance Options and Data Port Parameters Screen</i>	34
<i>Figure 3-3: Optional Flags, Handshaking, and Initialization Options Screen</i>	36
<i>Figure 3-4: Programmable Flags Screen</i>	38
<i>Figure 3-5: Data Count and Reset Screen</i>	40
<i>Figure 3-6: Summary Screen</i>	42

Chapter 4: Designing with the Core

<i>Figure 4-1: FIFO with Independent Clocks: Write and Read Clock Domains</i>	44
<i>Figure 4-2: Functional Implementation of a FIFO with Independent Clock Domains</i> ..	45
<i>Figure 4-3: Functional Implementation of Built-in FIFO</i>	47
<i>Figure 4-4: Functional Implementation of a Common Clock FIFO using Block RAM or Distributed RAM</i>	48
<i>Figure 4-5: Functional Implementation of a Common Clock FIFO using Shift Registers</i>	49
<i>Figure 4-6: Write Operation for a FIFO with Independent Clocks</i>	50
<i>Figure 4-7: Standard Read Operation for a FIFO with Independent Clocks</i>	52
<i>Figure 4-8: FWFT Read Operation for a FIFO with Independent Clocks</i>	52
<i>Figure 4-9: Write and Read Operation for a FIFO with Common Clocks</i>	53
<i>Figure 4-10: Handshaking Signals for a FIFO with Independent Clocks</i>	55
<i>Figure 4-11: Handshaking Signals for a FIFO with Common Clocks</i>	56
<i>Figure 4-12: Programmable Full Single Threshold: Threshold Set to 7</i>	58
<i>Figure 4-13: Programmable Full with Assert and Negate Thresholds: Assert Set to 10 and Negate Set to 7</i>	59
<i>Figure 4-14: Programmable Empty with Single Threshold: Threshold Set to 4</i>	60
<i>Figure 4-15: Programmable Empty with Assert and Negate Thresholds: Assert Set to 7 and Negate Set to 10</i>	61
<i>Figure 4-16: Write and Read Data Counts for FIFO with Independent Clocks</i>	65
<i>Figure 4-17: 1:4 Aspect Ratio: Data Ordering</i>	66
<i>Figure 4-18: 1:4 Aspect Ratio: Status Flag Behavior</i>	67
<i>Figure 4-19: 4:1 Aspect Ratio: Data Ordering</i>	67
<i>Figure 4-20: 4:1 Aspect Ratio: Status Flag Behavior</i>	68
<i>Figure 4-21: Standard Read Operation for a block RAM or built-in FIFO with Use Embedded Registers Enabled</i>	69
<i>Figure 4-22: FWFT Read Operation for a Synchronous Built-in FIFO with User Embedded Registers Enabled</i>	70
<i>Figure 4-23: SBITERR and DBITERR Outputs in the FIFO Generator Core</i>	71

<i>Figure 4-24: Block RAM, Distributed RAM, Shift RAM with Full Flags Reset Value of 1</i>	73
<i>Figure 4-25: Block RAM, Distributed RAM, Shift RAM with Full Flags Reset Value of 0</i>	74
<i>Figure 4-26: Built-in FIFO, Asynchronous Reset Behavior</i>	75
<i>Figure 4-27: Synchronous Reset: FIFO with a Common Clock</i>	75

Schedule of Tables

Chapter 2: Core Overview

<i>Table 2-1: Memory Configuration Benefits</i>	18
<i>Table 2-2: FIFO Configurations</i>	19
<i>Table 2-3: FIFO Configurations Summary</i>	20
<i>Table 2-4: Reset Signal for FIFOs with Independent Clocks</i>	22
<i>Table 2-5: Write Interface Signals for FIFOs with Independent Clocks</i>	23
<i>Table 2-6: Read Interface Signals for FIFOs with Independent Clocks</i>	24
<i>Table 2-7: Interface Signals for FIFOs with a Common Clock</i>	26

Chapter 4: Designing with the Core

<i>Table 4-1: Interface Signals and Corresponding Clock Domains</i>	46
<i>Table 4-2: Interface Signals and Corresponding Clock Domains</i>	47
<i>Table 4-3: Implementation-Specific Support for First-Word Fall-Through</i>	51
<i>Table 4-4: Implementation-specific Support for Data Counts</i>	62
<i>Table 4-5: Empty FIFO WR_DATA_COUNT/DATA_COUNT Value</i>	64
<i>Table 4-6: Implementation-specific Support for Non-symmetric Aspect Ratios</i>	65
<i>Table 4-7: FIFO Asynchronous Reset Values for block RAM, Distributed RAM, and Shift RAM FIFOs</i>	72
<i>Table 4-8: Asynchronous FIFO Reset Values for Built-in FIFO</i>	75
<i>Table 4-9: Synchronous FIFO Reset and Power-up Values</i>	76
<i>Table 4-10: Write Port Flags Update Latency Due to Write Operation</i>	78
<i>Table 4-11: Read Port Flags Update Latency Due to Read Operation</i>	78
<i>Table 4-12: Write Port Flags Update Latency Due to Read Operation</i>	79
<i>Table 4-13: Read Port Flags Update Latency Due to Write Operation</i>	79
<i>Table 4-14: Write Port Flags Update Latency due to Write Operation</i>	79
<i>Table 4-15: Read Port Flags Update Latency due to Read Operation</i>	80
<i>Table 4-16: Write Port Flags Update Latency Due to Read Operation</i>	80
<i>Table 4-17: Read Port Flags Update Latency Due to Write Operation</i>	81
<i>Table 4-18: Write Port Flags Update Latency Due to a Write Operation</i>	81
<i>Table 4-19: Read Port Flags Update Latency Due to a Read Operation</i>	81
<i>Table 4-20: Write Port Flags Update Latency Due to a Read Operation</i>	82
<i>Table 4-21: Read Port Flags Update Latency Due to a Write Operation</i>	82
<i>Table 4-22: Write Port Flags Update Latency Due to a Write Operation</i>	82
<i>Table 4-23: Read Port Flags Update Latency Due to a Read Operation</i>	83
<i>Table 4-24: Write Port Flags Update Latency Due to a Read Operation</i>	83
<i>Table 4-25: Read Port Flags Update Latency Due to a Write Operation</i>	83
<i>Table 4-26: Write Port Flags Update Latency Due to Write Operation</i>	84
<i>Table 4-27: Read Port Flags Update Latency Due to Read Operation</i>	84
<i>Table 4-28: Write Port Flags Update Latency Due to Read Operation</i>	84

<i>Table 4-29: Read Port Flags Update Latency Due to Write Operation</i>	85
<i>Table 4-30: Write Port Flags Update Latency Due to Write Operation.</i>	85
<i>Table 4-31: Read Port Flags Update Latency Due to a Read Operation</i>	85
<i>Table 4-32: Write Port Flags Update Latency Due to a Read Operation</i>	85
<i>Table 4-33: Read Port Flags Update Latency Due to a Write Operation</i>	86
<i>Table 4-34: Write Port Flags Update Latency Due to a Write Operation</i>	86
<i>Table 4-35: Read Port Flags Update Latency Due to a Read Operation</i>	87
<i>Table 4-36: Write Port Flags Update Latency Due to a Read Operation</i>	87
<i>Table 4-37: Read Port Flags Update Latency Due to a Write Operation</i>	87
<i>Table 4-38: Write Port Flags Update Latency Due to a Write Operations</i>	87
<i>Table 4-39: Read Port Flags Update Latency Due to a Read Operation</i>	88
<i>Table 4-40: Write Port Flags Update Latency Due to a Read Operation</i>	88
<i>Table 4-41: Read Port Flags Update Latency Due to a Write Operation</i>	88

Appendix A: Performance Information

<i>Table A-1: Benchmarks: FIFO Configured without Optional Features</i>	95
<i>Table A-2: Benchmarks: FIFO Configured with Multiple Programmable Thresholds</i> .	96
<i>Table A-3: Benchmarks: FIFO Configured with Virtex-5 FIFO36 Resources.</i>	97
<i>Table A-4: Benchmarks: FIFO Configured with Virtex-4 FIFO16 Patch</i>	98

Appendix B: Core Parameters

<i>Table B-1: FIFO Parameter Table</i>	99
--	----

About This Guide

The *LogicCORE™ IP FIFO Generator User Guide* describes the function and operation of the FIFO Generator, as well as information about designing, customizing, and implementing the core.

Guide Contents

The following chapters are included:

- [“Preface, About this Guide”](#) describes how the user guide is organized and the conventions used in this guide.
- [Chapter 1, “Introduction,”](#) describes the core and related information, including recommended design experience, additional resources, technical support, and submitting feedback to Xilinx.
- [Chapter 2, “Core Overview,”](#) describes the core configuration options and their interfaces.
- [Chapter 3, “Generating the Core,”](#) describes how to generate the core using the Xilinx CORE Generator Graphical User Interface (GUI).
- [Chapter 4, “Designing with the Core,”](#) discusses how to use the core in a user application.
- [Chapter 5, “Special Design Considerations,”](#) discusses specific design features that must be considered when designing with the core.
- [Chapter 6, “Simulating Your Design,”](#) provides instructions for simulating the design with either behavioral or structural simulation models.
- [Appendix A, “Performance Information,”](#) provides a summary of the core’s performance data.
- [Appendix B, “Core Parameters,”](#) provides a comprehensive list of the parameters set by the CORE Generator GUI for the FIFO Generator.

Conventions

This document uses the following conventions. An example illustrates each convention.

Typographical

The following typographical conventions are used in this document:

Convention	Meaning or Use	Example
Courier font	Messages, prompts, and program files that the system displays and signal names	speed grade: - 100
Courier bold	Literal commands you enter in a syntactical statement	ngdbuild design_name
Angle brackets < >	Variables in a syntax statement for which you must supply values	<design_name>
<i>Italic font</i>	References to other manuals	See the <i>FIFO Generator Data Sheet</i> for details.
	Emphasis in text	If a wire is drawn so that it overlaps the pin of a symbol, the two nets are <i>not</i> connected.
Dark Shading	Items that are not supported or reserved items	This feature is not supported
Square brackets []	An optional entry or parameter. However, in bus specifications, such as bus[7:0] , they are required.	ngdbuild [option_name] design_name
Braces { }	A list of items from which you must choose one or more	lowpwr = {on off}
Vertical bar	Separates items in a list of choices	lowpwr = {on off}
Vertical ellipsis .	Repetitive material that has been omitted	IOB #1: Name = QOUT' IOB #2: Name = CLKIN' . . .
Horizontal ellipsis ...	Omitted repetitive material	allow block block_name loc1 loc2 ... locn;
Notations	The prefix '0x' or the suffix 'h' indicate hexadecimal notation	A read of address 0x00112975 returned 45524943h.
	An '_n' means the signal is active low	usr_teof_n is active low.

Online Document

The following linking conventions are used in this document:

Convention	Meaning or Use	Example
Blue text	Cross-reference link to a location in the current document	See “ Additional Resources ” for more information.
Blue, underlined text	Hyperlink to a website (URL)	Go to www.xilinx.com for the latest speed files.

Introduction

The FIFO Generator core is a fully verified first-in first-out memory queue for use in any application requiring in-order storage and retrieval, enabling high-performance and area-optimized designs. This core can be customized using the Xilinx CORE Generator™ system as a complete solution with control logic already implemented, including management of the read and write pointers and the generation of status flags.

This chapter introduces the FIFO Generator and provides related information, including recommended design experience, additional resources, technical support, and submitting feedback to Xilinx.

About the Core

The FIFO Generator is a Xilinx CORE Generator IP core, included in the latest IP Update on the Xilinx IP Center. The core is free of charge and no license is required. For detailed information about the core, see the [FIFO Generator product page](#).

Windows

- Windows XP® Professional 32-bit/64-bit
- Windows Vista® Business 32-bit/64-bit

Linux

- Red Hat® Enterprise WS 4.0 32-bit/64-bit
- Red Hat Enterprise Desktop 5.0 32-bit/64-bit (with Workstation option)
- SUSE Linux Enterprise (SLE) v10.1 32-bit/64-bit

Software

- ISE® 10.1

Recommended Design Experience

The FIFO Generator is a fully verified solution, and can be used by all levels of design engineers.

Important: When implementing a FIFO with independent write and read clocks, special care must be taken to ensure the FIFO Generator is correctly used. “[Synchronization Considerations](#),” page 43 provides important information to help ensure correct design configuration.

Similarly, asynchronous designs should also be aware that the behavioral models are not cycle-accurate across clock domains. See [Chapter 6, “Simulating Your Design,”](#) for details.

Technical Support

For technical support, visit www.support.xilinx.com/. Questions are routed to a team of engineers with FIFO Generator expertise.

Xilinx will provide technical support for use of this product as described in the *LogiCORE FIFO Generator User Guide*. Xilinx cannot guarantee timing, functionality, or support of this product for designs that do not follow these guidelines.

Feedback

Xilinx welcomes comments and suggestions about the FIFO Generator and the documentation supplied with the core.

FIFO Generator

For comments or suggestions about the FIFO Generator, please submit a WebCase from www.support.xilinx.com/. Be sure to include the following information:

- Product name
- Core version number
- Explanation of your comments

Document

For comments or suggestions about this document, please submit a WebCase from www.support.xilinx.com/. Be sure to include the following information:

- Document title
- Document number
- Page number(s) to which your comments refer
- Explanation of your comments

Core Overview

This chapter provides an overview of the FIFO Generator configuration options and interfaces.

Feature Overview

Clock Implementation Operation

The FIFO Generator enables FIFOs to be configured with either independent or common clock domains for write and read operations. The independent clock configuration of the FIFO Generator enables the user to implement unique clock domains on the write and read ports. The FIFO Generator handles the synchronization between clock domains, placing no requirements on phase and frequency relationships between clocks. A common clock domain implementation optimizes the core for data buffering within a single clock domain.

Virtex-5 FPGA Built-in FIFO Support

The FIFO Generator supports the VirtexTM-5 FPGA built-in FIFO modules, enabling the creation of large FIFOs by cascading the built-in FIFOs in both width and depth. The core expands the capabilities of the built-in FIFOs by utilizing the FPGA fabric to create optional status flags not implemented in the built-in FIFO macro. The built-in Error Correction Checking (ECC) feature in the built-in FIFO macro is also available.

Virtex-4 FPGA Built-in FIFO Support

The FIFO Generator supports a single instantiation of the Virtex-4 FPGA built-in FIFO module. The core also implements a FIFO flag patch (“Solution 1: Synchronous/Asynchronous Clock Work-Arounds,” defined in the *Virtex-4 FPGA User Guide*), based on estimated clock frequencies. This patch is implemented in fabric. See [Appendix A, “Performance Information”](#) for resource utilization estimates.

First-Word Fall-Through

The first-word fall-through (FWFT) feature provides the ability to look ahead to the next word available from the FIFO without having to issue a read operation. The FIFO accomplishes this by using output registers which are automatically loaded with data, when data appears in the FIFO. This causes the first word written to the FIFO to automatically appear on the data out bus (DOUT). Subsequent user read operations cause the output data to update with the next word, as long as data is available in the FIFO. The use of registers on the FIFO DOUT bus improves clock-to-output timing, and the FWFT

functionality provides low-latency access to data. This is ideal for applications that require throttling, based on the contents of the data that are read.

See [Table 2-2](#) for FWFT availability. The use of this feature impacts the behavior of many other features, such as:

- Read operations (see [“First-Word-Fall-Through FIFO Read Operation,”](#) page 52)
- Programmable empty (see [“Non-symmetric Aspect Ratio and First-Word Fall-Through,”](#) page 68)
- Data counts (see [“First-Word Fall-Through Data Count,”](#) page 63 and [“Non-symmetric Aspect Ratio and First-Word Fall-Through,”](#) page 68)

Memory Types

The FIFO Generator implements FIFOs built from block RAM, distributed RAM, shift registers, or the built-in FIFOs for Virtex-4 and Virtex-5 FPGAs. The core combines memory primitives in an optimal configuration based on the selected width and depth of the FIFO. [Table 2-1](#) provides best-use recommendations for specific design requirements.

Table 2-1: Memory Configuration Benefits

	Independent Clocks	Common Clock	Small Buffering	Medium-Large Buffering	High Performance	Minimal Resources
Built-in FIFO	✓	✓		✓	✓	✓
block RAM	✓	✓		✓	✓	✓
Shift Register		✓	✓		✓	
Distributed RAM	✓	✓	✓		✓	

Non-Symmetric Aspect Ratio

The core supports generating FIFOs whose write and read ports have different widths, enabling automatic width conversion of the data width. Non-symmetric aspect ratios ranging from 1:8 to 8:1 are supported for the write and read port widths. This feature is available for FIFOs implemented with block RAM that are configured to have independent write and read clocks.

Embedded Registers in block RAM and FIFO Macros (Virtex-4 and Virtex-5 Devices)

In Virtex-4 and Virtex-5 FPGA block RAM and FIFO macros, embedded output registers are available to increase performance and add a pipeline register to the macros. This feature can be leveraged to add one additional latency to the FIFO core (DOUT bus and VALID outputs) or implement the output registers for FWFT FIFOs. See [“Embedded Registers in block RAM and FIFO Macros \(Virtex-4 and Virtex-5 FPGAs\),”](#) page 69 for more information.

Error Correction Checking

For the Virtex-5 FPGA architecture, the block RAM and FIFO macros are equipped with built-in Error Correction Checking (ECC), available for both the common and independent clock block RAM or built-in based FIFOs.

Core Configuration and Implementation

Table 2-2 provides a summary of the supported memory and clock configurations.

Table 2-2: FIFO Configurations

Clock Domain	Memory Type	Non-symmetric Aspect Ratios	First-Word Fall-Through	ECC Support	Embedded Register Support
Common	block RAM		✓	✓	✓ ¹
Common	Distributed RAM		✓		
Common	Shift Register				
Common	Built-in FIFO ²		✓ ³	✓	✓ ⁴
Independent	block RAM	✓	✓	✓	✓ ¹
Independent	Distributed RAM		✓		
Independent	Built-in FIFO ^{2,5}		✓ ³	✓	

1. Embedded register support is only available for Virtex-4 and Virtex-5 FPGA block RAM-based FIFOs.
2. The built-in FIFO primitive is only available in the Virtex-5 and Virtex-4 architectures.
3. FWFT is only supported for built-in FIFOs in Virtex-5 devices.
4. Only available for Virtex-5 FPGA common clock built-in FIFOs.
5. For non-symmetric aspect ratios, use the block RAM implementation (feature not supported in built-in FIFO primitive).

Common Clock: Block RAM, Distributed RAM, Shift Register

This implementation category allows the user to select block RAM, distributed RAM, or shift register and supports a common clock for write and read data accesses.

The feature set supported for this configuration includes status flags (full, almost full, empty, and almost empty) and programmable empty and full flags generated with user-defined thresholds. In addition, optional handshaking and error flags are supported (write acknowledge, overflow, valid, and underflow), and an optional data count provides the number of words in the FIFO. In addition, for the block RAM and distributed RAM implementations, the user has the option to select a synchronous or asynchronous reset for the core. For Virtex-5 FPGA designs, the block RAM FIFO configuration also supports ECC.

Common Clock: Virtex-5 or Virtex-4 FPGA Built-in FIFO

This implementation category allows the user to select the built-in FIFO available in the Virtex-5 or Virtex-4 FPGA architectures and supports a common clock for write and read data accesses.

The feature set supported for this configuration includes status flags (full and empty) and optional programmable full and empty flags with user-defined thresholds. In addition, optional handshaking and error flags are available (write acknowledge, overflow, valid, and underflow). The Virtex-5 FPGA built-in FIFO configuration also supports the built-in ECC feature.

Independent Clocks: Block RAM and Distributed RAM

This implementation category allows the user to select block RAM or distributed RAM and supports independent clock domains for write and read data accesses. Operations in the read domain are synchronous to the read clock and operations in the write domain are synchronous to the write clock.

The feature set supported for this type of FIFO includes non-symmetric aspect ratios (different write and read port widths), status flags (full, almost full, empty, and almost empty), as well as programmable full and empty flags generated with user-defined thresholds. Optional read data count and write data count indicators provide the number of words in the FIFO relative to their respective clock domains. In addition, optional handshaking and error flags are available (write acknowledge, overflow, valid, and underflow). For Virtex-5 FPGA designs, the block RAM FIFO configuration also supports ECC.

Independent Clocks: Built-in FIFO for Virtex-5 or Virtex-4 FPGAs

This implementation category allows the user to select the built-in FIFO available in the Virtex-5 or Virtex-4 FPGA architectures. Operations in the read domain are synchronous to the read clock and operations in the write domain are synchronous to the write clock.

The feature set supported for this configuration includes status flags (full and empty) and programmable full and empty flags generated with user-defined thresholds. In addition, optional handshaking and error flags are available (write acknowledge, overflow, valid, and underflow). The Virtex-5 FPGA built-in FIFO configuration also supports the built-in ECC feature.

FIFO Generator Features

Table 2-3 summarizes the FIFO Generator features supported for each clock configuration and memory type.

Table 2-3: FIFO Configurations Summary

FIFO Feature	Independent Clocks			Common Clock		
	Block RAM	Distributed RAM	Built-in FIFO ¹	Block RAM	DistributedRAM, Shift Register	Built-in FIFO ¹
Non-symmetric Aspect Ratios ²	✓					
Symmetric Aspect Ratios	✓	✓	✓	✓	✓	✓
Almost Full	✓	✓		✓	✓	
Almost Empty	✓	✓		✓	✓	

Table 2-3: FIFO Configurations Summary (Continued)

FIFO Feature	Independent Clocks			Common Clock		
	Block RAM	Distributed RAM	Built-in FIFO ¹	Block RAM	DistributedRAM, Shift Register	Built-in FIFO ¹
Handshaking	✓	✓	✓	✓	✓	✓
Data Count	✓	✓		✓	✓	
Programmable Empty/Full Thresholds	✓	✓	✓ ³	✓	✓	✓ ³
First-Word Fall-Through	✓	✓	✓ ⁴	✓	✓ ⁵	✓ ⁴
Synchronous Reset				✓	✓ ⁶	
Asynchronous Reset	✓ ⁷	✓ ⁷	✓	✓ ⁷	✓ ⁷	✓
DOUT Reset Value	✓ ⁸	✓		✓ ⁸	✓	
ECC	✓ ⁹		✓ ⁹	✓ ⁹		✓ ⁹
Embedded Register	✓ ¹⁰			✓ ¹⁰		✓ ¹¹

1. For Virtex-4 FPGA Built-in FIFO macro, the valid width range is 4, 9, 18 and 36 and the valid depth range automatically varies based on write width selection. For Virtex-5 FPGA Built-in FIFO macro, the valid width range is 1 to 1024 and the valid depth range is 512 to 4194304. Only depths with powers of 2 are allowed.
2. For applications with a single clock that require non-symmetric ports, use the independent clock configuration and connect the write and read clocks to the same source. A dedicated solution for common clocks will be available in a future release. Contact your Xilinx representative for more details.
3. For built-in FIFOs, the range of Programmable Empty/Full threshold is limited to take advantage of the logic internal to the macro.
4. First-Word-Fall-Through is only supported for the Virtex-5 FPGA built-in FIFOs.
5. First-Word-Fall-Through is supported for distributed RAM FIFO only.
6. Synchronous reset is available and optional for common clock configurations using distributed and block RAM only.
7. Asynchronous reset is optional for all FIFOs built using distributed and block RAM.
8. All architectures except Virtex, Virtex-E, Spartan-II, and Spartan-IIE FPGAs.
9. ECC is only supported for the Virtex-5 FPGA and block RAM and built-in FIFOs.
10. Embedded register option is only supported in Virtex-4 and Virtex-5 FPGA block RAM FIFOs.
11. Embedded register option is supported only in Virtex-5 FPGA common clock built-in FIFOs. See **Embedded Registers in block RAM and FIFO Macros (Virtex-4 and Virtex-5 Devices)**.


Using Block RAM FIFOs Instead of Built-in FIFOs

The Built-In FIFO solutions were implemented to take advantage of logic internal to the Built-in FIFO macro. Several features, for example, non-symmetric aspect ratios, almost full, almost empty, and so forth were not implemented because they are not native to the macro and require additional logic in the fabric to implement.

Benchmarking suggests that the advantages the Built-In FIFO implementations have over the block RAM FIFOs (for example, logic resources) diminish as external logic is added to implement features not native to the macro. This is especially true as the depth of the implemented FIFO increases. It is strongly recommended that users requiring features not available in the Built-In FIFOs implement their design using block RAM FIFOs.

FIFO Interfaces

The following two sections provide definitions for the FIFO interface signals. [Figure 2-1](#) illustrates these signals (both the standard and optional ports) for a FIFO core that supports independent write and read clocks.



Note: Optional ports represented in *italics*

Figure 2-1: FIFO with Independent Clocks: Interface Signals

Interface Signals: FIFOs With Independent Clocks

The RST signal, as defined in [Table 2-4](#), causes a reset of the entire core logic (both write and read clock domains). It is an asynchronous input which is synchronized internally in the core before being used. The initial hardware reset should be generated by the user. When the core is configured to have independent clocks, the reset signal should be High for at least three read clock and write clock cycles to ensure all internal states are reset to the correct values.

Table 2-4: Reset Signal for FIFOs with Independent Clocks

Name	Direction	Description
RST	Input	Reset: An asynchronous reset signal that initializes all internal pointers, output registers and memory ¹ .

1. Output of FIFO (DOUT) is reset and not the content of the memory.

Table 2-5 defines the signals for the write interface for FIFOs with independent clocks. The write interface signals are divided into required and optional signals and all signals are synchronous to the write clock (WR_CLK).

Table 2-5: Write Interface Signals for FIFOs with Independent Clocks

Name	Direction	Description
<i>Required</i>		
WR_CLK	Input	Write Clock: All signals on the write domain are synchronous to this clock.
DIN[N:0]	Input	Data Input: The input data bus used when writing the FIFO.
WR_EN	Input	Write Enable: If the FIFO is not full, asserting this signal causes data (on DIN) to be written to the FIFO.
FULL	Output	Full Flag: When asserted, this signal indicates that the FIFO is full. Write requests are ignored when the FIFO is full, initiating a write when the FIFO is full is non-destructive to the contents of the FIFO.
<i>Optional</i>		
ALMOST_FULL	Output	Almost Full: When asserted, this signal indicates that only one more write can be performed before the FIFO is full.
PROG_FULL	Output	Programmable Full: This signal is asserted when the number of words in the FIFO is greater than or equal to the assert threshold. It is deasserted when the number of words in the FIFO is less than the negate threshold.
WR_DATA_COUNT [D:0]	Output	Write Data Count: This bus indicates the number of words written into in the FIFO. The count is guaranteed to never under-report the number of words in the FIFO, to ensure the user never overflows the FIFO. The exception to this behavior is when a write operation occurs at the rising edge of WR_CLK, that write operation will only be reflected on WR_DATA_COUNT at the next rising clock edge. If D is less than $\log_2(\text{FIFO depth})-1$, the bus is truncated by removing the least-significant bits.
WR_ACK	Output	Write Acknowledge: This signal indicates that a write request (WR_EN) during the prior clock cycle succeeded.
OVERFLOW	Output	Overflow: This signal indicates that a write request (WR_EN) during the prior clock cycle was rejected, because the FIFO is full. Overflowing the FIFO is non-destructive to the contents of the FIFO.

Table 2-5: Write Interface Signals for FIFOs with Independent Clocks (Continued)

Name	Direction	Description
PROG_FULL_THRESH	Input	<p>Programmable Full Threshold: This signal is used to input the threshold value for the assertion and deassertion of the programmable full (PROG_FULL) flag. The threshold can be dynamically set in-circuit during reset.</p> <p>The user can either choose to set the assert and negate threshold to the same value (using PROG_FULL_THRESH), or the user can control these values independently (using PROG_FULL_THRESH_ASSERT and PROG_FULL_THRESH_NEGATE).</p>
PROG_FULL_THRESH_ASSERT	Input	<p>Programmable Full Threshold Assert: This signal is used to set the upper threshold value for the programmable full flag, which defines when the signal is asserted. The threshold can be dynamically set in-circuit during reset.</p>
PROG_FULL_THRESH_NEGATE	Input	<p>Programmable Full Threshold Negate: This signal is used to set the lower threshold value for the programmable full flag, which defines when the signal is deasserted. The threshold can be dynamically set in-circuit during reset.</p>

Table 2-6 defines the signals on the read interface of a FIFO with independent clocks. The read interface signals are divided into required signals and optional signals, and all signals are synchronous to the read clock (RD_CLK).

Table 2-6: Read Interface Signals for FIFOs with Independent Clocks

Name	Direction	Description
<i>Required</i>		
RD_CLK	Input	Read Clock: All signals on the read domain are synchronous to this clock.
DOUT[M:0]	Output	Data Output: The output data bus is driven when reading the FIFO.
RD_EN	Input	Read Enable: If the FIFO is not empty, asserting this signal causes data to be read from the FIFO (output on DOUT).
EMPTY	Output	Empty Flag: When asserted, this signal indicates that the FIFO is empty. Read requests are ignored when the FIFO is empty, initiating a read while empty is non-destructive to the FIFO.
<i>Optional</i>		
ALMOST_EMPTY	Output	Almost Empty Flag: When asserted, this signal indicates that the FIFO is almost empty and one word remains in the FIFO.

Table 2-6: Read Interface Signals for FIFOs with Independent Clocks (Continued)

Name	Direction	Description
PROG_EMPTY	Output	Programmable Empty: This signal is asserted when the number of words in the FIFO is less than or equal to the programmable threshold. It is deasserted when the number of words in the FIFO exceeds the programmable threshold.
RD_DATA_COUNT [C:0]	Output	Read Data Count: This bus indicates the number of words available for reading in the FIFO. The count is guaranteed to never over-report the number of words available for reading, to ensure that the user does not underflow the FIFO. The exception to this behavior is when the read operation occurs at the rising edge of RD_CLK, that read operation will only be reflected on RD_DATA_COUNT at the next rising clock edge. If C is less than $\log_2(\text{FIFO depth})-1$, the bus is truncated by removing the least-significant bits.
VALID	Output	Valid: This signal indicates that valid data is available on the output bus (DOUT).
UNDERFLOW	Output	Underflow: Indicates that the read request (RD_EN) during the previous clock cycle was rejected because the FIFO is empty. Underflowing the FIFO is not destructive to the FIFO.
PROG_EMPTY_THRESH	Input	Programmable Empty Threshold: This signal is used to input the threshold value for the assertion and deassertion of the programmable empty (PROG_EMPTY) flag. The threshold can be dynamically set in-circuit during reset. The user can either choose to set the assert and negate threshold to the same value (using PROG_EMPTY_THRESH), or the user can control these values independently (using PROG_EMPTY_THRESH_ASSERT and PROG_EMPTY_THRESH_NEGATE).
PROG_EMPTY_THRESH_ASSERT	Input	Programmable Empty Threshold Assert: This signal is used to set the lower threshold value for the programmable empty flag, which defines when the signal is asserted. The threshold can be dynamically set in-circuit during reset.
PROG_EMPTY_THRESH_NEGATE	Input	Programmable Empty Threshold Negate: This signal is used to set the upper threshold value for the programmable empty flag, which defines when the signal is deasserted. The threshold can be dynamically set in-circuit during reset.

Table 2-6: Read Interface Signals for FIFOs with Independent Clocks (Continued)

Name	Direction	Description
SBITERR	Output	Single Bit Error: Indicates that the ECC decoder detected and fixed a single-bit error on a Virtex-5 FPGA block RAM or built-in FIFO macro. See “ Built-in Error Correction Checking ,” page 70.
DBITERR	Output	Double Bit Error: Indicates that the ECC decoder detected a double-bit error on a Virtex-5 FPGA block RAM or built-in FIFO macro and data in the FIFO core is corrupted. See “ Built-in Error Correction Checking ,” page 70.

Interface Signals: FIFOs with Common Clock

Table 2-7 defines the interface signals of a FIFO with a common write and read clock. The table is divided into standard and optional interface signals, and all signals (except reset) are synchronous to the common clock (CLK). Users have the option to select synchronous or asynchronous reset for the distributed or block RAM FIFO implementation.

Table 2-7: Interface Signals for FIFOs with a Common Clock

Name	Direction	Description
<i>Required</i>		
RST	Input	Reset: An asynchronous reset that initializes all internal pointers and output registers.
SRST	Input	Synchronous Reset: A synchronous reset that initializes all internal pointers and output registers.
CLK	Input	Clock: All signals on the write and read domains are synchronous to this clock.
DIN[N:0]	Input	Data Input: The input data bus used when writing the FIFO.
WR_EN	Input	Write Enable: If the FIFO is not full, asserting this signal causes data (on DIN) to be written to the FIFO.
FULL	Output	Full Flag: When asserted, this signal indicates that the FIFO is full. Write requests are ignored when the FIFO is full, initiating a write when the FIFO is full is non-destructive to the contents of the FIFO.
DOUT[M:0]	Output	Data Output: The output data bus driven when reading the FIFO.
RD_EN	Input	Read Enable: If the FIFO is not empty, asserting this signal causes data to be read from the FIFO (output on DOUT).

Table 2-7: Interface Signals for FIFOs with a Common Clock (Continued)

Name	Direction	Description
EMPTY	Output	Empty Flag: When asserted, this signal indicates that the FIFO is empty. Read requests are ignored when the FIFO is empty, initiating a read while empty is non-destructive to the FIFO.
<i>Optional</i>		
DATA_COUNT [C:0]	Output	Data Count: This bus indicates the number of words stored in the FIFO. If C is less than $\log_2(\text{FIFO depth})-1$, the bus is truncated by removing the least-significant bits.
ALMOST_FULL	Output	Almost Full: When asserted, this signal indicates that only one more write can be performed before the FIFO is full.
PROG_FULL	Output	Programmable Full: This signal is asserted when the number of words in the FIFO is greater than or equal to the assert threshold. It is deasserted when the number of words in the FIFO is less than the negate threshold.
WR_ACK	Output	Write Acknowledge: This signal indicates that a write request (WR_EN) during the prior clock cycle succeeded.
OVERFLOW	Output	Overflow: This signal indicates that a write request (WR_EN) during the prior clock cycle was rejected, because the FIFO is full. Overflowing the FIFO is non-destructive to the contents of the FIFO.
PROG_FULL_THRESH	Input	<p>Programmable Full Threshold: This signal is used to set the threshold value for the assertion and deassertion of the programmable full flag (PROG_FULL). The threshold can be dynamically set in-circuit during reset.</p> <p>The user can either choose to set the assert and negate threshold to the same value (using PROG_FULL_THRESH), or the user can control these values independently (using PROG_FULL_THRESH_ASSERT and PROG_FULL_THRESH_NEGATE).</p>
PROG_FULL_THRESH_ASSERT	Input	Programmable Full Threshold Assert: This signal is used to set the upper threshold value for the programmable full flag, which defines when the signal is asserted. The threshold can be dynamically set in-circuit during reset.

Table 2-7: Interface Signals for FIFOs with a Common Clock (Continued)

Name	Direction	Description
PROG_FULL_THRESH_NEGATE	Input	Programmable Full Threshold Negate: This signal is used to set the lower threshold value for the programmable full flag, which defines when the signal is deasserted. The threshold can be dynamically set in-circuit during reset.
ALMOST_EMPTY	Output	Almost Empty Flag: When asserted, this signal indicates that the FIFO is almost empty and one word remains in the FIFO.
PROG_EMPTY	Output	Programmable Empty: This signal is asserted after the number of words in the FIFO is less than or equal to the programmable threshold. It is deasserted when the number of words in the FIFO exceeds the programmable threshold.
VALID	Output	Valid: This signal indicates that valid data is available on the output bus (DOUT).
UNDERFLOW	Output	Underflow: Indicates that read request (RD_EN) during the previous clock cycle was rejected because the FIFO is empty. Underflowing the FIFO is not destructive to the FIFO.
PROG_EMPTY_THRESH	Input	<p>Programmable Empty Threshold: This signal is used to set the threshold value for the assertion and deassertion of the programmable empty flag (PROG_EMPTY). The threshold can be dynamically set in-circuit during reset.</p> <p>The user can either choose to set the assert and negate threshold to the same value (using PROG_EMPTY_THRESH), or the user can control these values independently (using PROG_EMPTY_THRESH_ASSERT and PROG_EMPTY_THRESH_NEGATE).</p>
PROG_EMPTY_THRESH_ASSERT	Input	Programmable Empty Threshold Assert: This signal is used to set the lower threshold value for the programmable empty flag, which defines when the signal is asserted. The threshold can be dynamically set in-circuit during reset.
PROG_EMPTY_THRESH_NEGATE	Input	Programmable Empty Threshold Negate: This signal is used to set the upper threshold value for the programmable empty flag, which defines when the signal is deasserted. The threshold can be dynamically set in-circuit during reset.

Table 2-7: Interface Signals for FIFOs with a Common Clock (Continued)

Name	Direction	Description
SBITERR	Output	Single Bit Error: Indicates that the ECC decoder detected and fixed a single-bit error on a Virtex-5 FPG built-in FIFO macro. See “Built-in Error Correction Checking,” page 70.
DBITERR	Output	Double Bit Error: Indicates that the ECC decoder detected a double-bit error on a Virtex-5 FPGA built-in FIFO macro, and data in the FIFO core is corrupted. See “Built-in Error Correction Checking,” page 70.

Generating the Core

This chapter contains information and instructions for using the Xilinx CORE Generator system to customize the FIFO Generator.

CORE Generator Graphical User Interface

The FIFO Generator GUI includes six configuration screens.

- [FIFO Implementation](#)
- [Performance Options and Data Port Parameters](#)
- [Optional Flags, Handshaking, and Initialization](#)
- [Initialization and Programmable Flags](#)
- [Data Count](#)
- [Summary](#)

FIFO Implementation

The main FIFO Generator screen is used to define the component name and provides configuration options for the core.




Figure 3-1: Main FIFO Generator Screen

Component Name

Base name of the output files generated for this core. The name must begin with a letter and be composed of the following characters: a to z, 0 to 9, and “_”.

FIFO Implementation

This section of the GUI allows the user to select from a set of available FIFO implementations and supported features. The key supported features that are only available for certain implementations are highlighted by checks in the right-margin. The available options are listed below, with cross-references to additional information.

Common Clock (CLK), Block RAM

For details, see [“Common Clock FIFO: Block RAM and Distributed RAM,” page 48](#). This implementation optionally supports first-word-fall-through (selectable in the second GUI screen, shown in [Figure 3-2](#)).

Common Clock (CLK), Distributed RAM

For details, see [“Common Clock FIFO: Block RAM and Distributed RAM,” page 48](#). This implementation optionally supports first-word-fall-through (selectable in the second GUI screen, shown in [Figure 3-2](#)).

Common Clock (CLK), Shift Register

For details, see [“Common Clock FIFO: Shift Registers,” page 48](#). This implementation is only available in Virtex-II FPGA and newer architectures.

Common Clock (CLK), Built-in FIFO

For details, see [“Common Clock: Built-in FIFO,” page 47](#). This implementation is only available when using the Virtex-5 or Virtex-4 FPGA architectures. This implementation optionally supports first-word fall-through (selectable in the second GUI screen, shown in [Figure 3-2](#)).

Independent Clocks (RD_CLK, WR_CLK), Block RAM

For details, see [“Independent Clocks: Block RAM and Distributed RAM,” page 45](#). This implementation optionally supports asymmetric read/write ports and first-word fall-through (selectable in the second GUI screen, shown in [Figure 3-2](#)).

Independent Clocks (RD_CLK, WR_CLK), Distributed RAM

For more information, see [“Independent Clocks: Block RAM and Distributed RAM,” page 45](#). This implementation optionally supports first-word fall-through (selectable in the second GUI screen, shown in [Figure 3-2](#)).

Independent Clocks (RD_CLK, WR_CLK), Built-in FIFO

For more information, see [“Independent Clocks: Built-in FIFO,” page 46](#). This implementation is only available when using Virtex-5 or Virtex-4 FPGA architectures. This implementation optionally supports first-word fall-through (selectable in the second GUI screen, shown in [Figure 3-2](#)).

Performance Options and Data Port Parameters

This screen provides performance options and data port parameters for the core.




Figure 3-2: Performance Options and Data Port Parameters Screen

Read Mode

Available only when block RAM or distributed RAM FIFOs are selected. Support for built-in FIFOs is only available for Virtex-5 FPGA implementations.

Standard FIFO

Implements a FIFO with standard latencies, and without using output registers.

First-Word Fall-Through FIFO

Implements a FIFO with registered outputs. For more information about FWFT functionality, see [“First-Word-Fall-Through FIFO Read Operation,”](#) page 52.

Built-in FIFO Options

Read/Write Clock Frequencies

The Read Clock Frequency and Write Clock Frequency fields can be any integer from 1 to 1000. They are used to determine the optimal implementation of the domain-crossing logic in the core. This option is only available for built-in FIFOs with independent clocks. If the desired frequency is not within the allowable range, scale the read and write clock frequencies so that they fit within the valid range, while maintaining their ratio relationship.

Important: It is critical that this information is entered and accurate. If this information is not provided, it can result in a sub-optimal solution with incorrect core behavior.

Data Port Parameters

Write Width

For Virtex-4 FPGA Built-in FIFO macro, the valid range is 4, 9, 18 and 36. For other memory type configurations, the valid range is 1 to 1024.

Write Depth

For Virtex-4 FPGA Built-in FIFO macro, the valid range automatically varies based on write width selection. For Virtex-5 FPGA Built-in FIFO macro, the valid range is 512 to 4194304. Only depths with powers of 2 are allowed.

For non Built-in FIFO, the valid range is 1 to 4194304. Only depths with powers of 2 are allowed.

Read Width

Available only if independent clocks configuration with block RAM is selected. Valid range must comply with asymmetric port rules. See [“Non-symmetric Aspect Ratios,” page 65](#).

Read Depth

Automatically calculated based on Write Width, Write Depth, and Read Width.

Implementation Options

Error Correction Checking

The Error Correction Checking (ECC) feature enables built-in error correction in the Virtex-5 FPGA built-in FIFO macro. When this feature is enabled, the built-in FIFO is set to the full ECC mode, where both the encoder and decoder are enabled.

Use Embedded Registers in Block RAM or FIFO

For Virtex-4 and Virtex-5 FPGA architectures, the built-in FIFO and block RAM macros have built-in embedded registers that can be used to pipeline data and improve macro timing. This option enables users to add one pipeline stage to the output of the FIFO and take advantage of the available embedded registers; however, the ability to reset the data

output of the FIFO is disabled when this feature is used. For built-in FIFOs, this feature is only supported for synchronous FIFO configurations that have only 1 FIFO macro in depth. See “Embedded Registers in block RAM and FIFO Macros (Virtex-4 and Virtex-5 FPGAs),” page 69.

Optional Flags, Handshaking, and Initialization

This screen allows you to select the optional status flags and set the handshaking options.




Figure 3-3: Optional Flags, Handshaking, and Initialization Options Screen

Optional Flags

Almost Full Flag

Available in all FIFO implementations except those using Virtex-5 or Virtex-4 FPGA built-in FIFOs. Generates an output port that indicates the FIFO is almost full (only one more word can be written).

Almost Empty Flag

Available in all FIFO implementations except in those using Virtex-5 or Virtex-4 FPGA built-in FIFOs. Generates an output port that indicates the FIFO is almost empty (only one more word can be read).

Handshaking Options

Write Port Handshaking

Write Acknowledge

Generates write acknowledge flag which reports the success of a write operation. This signal can be configured to be active high or low (default active high).

Overflow (Write Error)

Generates overflow flag which indicates when the previous write operation was not successful. This signal can be configured to be active high or low (default active high).

Read Port Handshaking

Valid (Read Acknowledge)

Generates valid flag which indicates when the data on the output bus is valid. This signal can be configured to be active high or low (default active high).

Underflow (Read Error)

Generates underflow flag to indicate that the previous read request was not successful. This signal can be configured to be active high or low (default active high).

Initialization and Programmable Flags

Use this screen to select the initialization values and programmable flag type when generating a specific FIFO Generator configuration.




Figure 3-4: Programmable Flags Screen

Initialization

Reset Pin

For FIFOs implemented with block RAM or distributed RAM, a reset pin is not required, and the input pin is optional.

- Asynchronous Reset. Optional selection for a common-clock FIFO implemented using distributed or block RAM.
- Synchronous Reset. Optional selection for a a common-clock FIFO implemented using distributed or block RAM.

Full Flags Reset Value

For block RAM, distributed RAM, and shift register configurations, the user can choose the reset value of the full flags (PROG_FULL, ALMOST_FULL, and FULL) during asynchronous reset.

Use Dout Reset

Available in Virtex-II FPGA or newer architectures for all implementations using block RAM, distributed RAM, or shift register. Only available if a reset pin (RST or SRST) is used. If selected, the DOUT output of the FIFO will reset to the defined DOUT Reset Value (below) when the reset is asserted. If not selected, the DOUT output of the FIFO will not be effected by the assertion of reset.

Disabling this feature for Spartan®-3 devices may improve timing for the distributed RAM and shift register FIFO.

Use Dout Reset Value

Available only when Use Dout Reset is selected, this field indicates the hexadecimal value asserted on the output of the FIFO when RST (SRST) is asserted.

Programmable Flags

Programmable Full Type

Select a programmable full threshold type from the drop-down menu. The valid range for each threshold is displayed and varies depending on the options selected elsewhere in the GUI.

Full Threshold Assert Value

Available when Programmable Full with Single or Multiple Threshold Constants is selected. Enter a user-defined value. The valid range for this threshold is provided in the GUI. When using a single threshold constant, only the assert threshold value is used.

Full Threshold Negate Value

Available when Programmable Full with Multiple Threshold Constants is selected. Enter a user-defined value. The valid range for this threshold is provided in the GUI.

Programmable Empty Type

Select a programmable empty threshold type from the drop-down menu. The valid range for each threshold is displayed, and will vary depending on options selected elsewhere in the GUI.

Empty Threshold Assert Value

Available when Programmable Empty with Single or Multiple Threshold Constants is selected. Enter a user-defined value. The valid range for this threshold is provided in the GUI. When using a single threshold constant, only the assert value is used.

Empty Threshold Negate Value

Available when Programmable Empty with Multiple Threshold Constants is selected. Enter a user-defined value. The valid range for this threshold is provided in the GUI.

Data Count

Use this screen to set data count options.




Figure 3-5: Data Count and Reset Screen

Data Count Options

Use Extra Logic For More Accurate Data Counts

Only available for independent clocks FIFO with block RAM or distributed RAM, and when using first-word fall-through. This option uses additional external logic to generate a more accurate data count. This feature is always enabled for common clock FIFOs with block RAM or distributed RAM and when using first-word-fall-through. See [“First-Word Fall-Through Data Count,”](#) page 63 for details.

Data Count (Synchronized With Clk)

Available when a common clock FIFO with block RAM, distributed RAM, or shift registers is selected.

Data Count Width

Available when Data Count is selected. Valid range is from 1 to \log_2 (input depth).

Write Data Count (Synchronized with Write Clk)

Available when an independent clocks FIFO with block RAM or distributed RAM is selected.

Write Data Count Width

Available when Write Data Count is selected. Valid range is from 1 to \log_2 (input depth).

Read Data Count (Synchronized with Read Clk)

Available when an independent clocks FIFO with block RAM or distributed RAM is selected.

Read Data Count Width

Available when Read Data Count is selected. Valid range is from 1 to \log_2 (output depth).

Summary

This screen displays a summary of the selected FIFO options, including the FIFO type, FIFO dimensions, and the status of any additional features selected. In the Additional Features section, most features display either *Not Selected* (if unused), or *Selected* (if used).

Note: Write depth and read depth provide the actual FIFO depths for the selected configuration. These depths may differ slightly from the depth selected on screen 2 of the FIFO GUI.




Figure 3-6: Summary Screen

Designing with the Core

This chapter describes the steps required to turn a FIFO Generator core into a fully functioning design integrated with the user application logic. It is important to note that depending on the configuration of the FIFO core, only a subset of the implementation details provided are applicable. For successful use of a FIFO core, the design guidelines discussed in this chapter must be observed.

General Design Guidelines

Know the Degree of Difficulty

A fully-compliant and feature-rich FIFO design is challenging to implement in any technology. For this reason, it is important to understand that the degree of difficulty can be significantly influenced by

- Maximum system clock frequency
- Targeted device architecture
- Specific user application

Ensure that design techniques are used to facilitate implementation, including pipelining and use of constraints (timing constraints, and placement and/or area constraints).

Understand Signal Pipelining and Synchronization

To understand the nature of FIFO designs, it is important to understand how pipelining is used to maximize performance and implement synchronization logic for clock-domain crossing. Data written into the write interface may take multiple clock cycles before it can be accessed on the read interface.

Synchronization Considerations

FIFOs with independent write and read clocks require that interface signals be used only in their respective clock domains. The independent clocks FIFO handles all synchronization requirements, enabling the user to cross between two clock domains that have no relationship in frequency or phase.

Important: FIFO Full and Empty flags must be used to guarantee proper behavior.

[Figure 4-1](#) shows the signals with respect to their clock domains. All signals are synchronous to a specific clock, with the exception of RST, which performs an asynchronous reset of the entire FIFO.




Figure 4-1: FIFO with Independent Clocks: Write and Read Clock Domains

For write operations, the write enable signal (*WR_EN*) and data input (*DIN*) are synchronous to *WR_CLK*. For read operations, the read enable (*RD_EN*) and data output (*DOUT*) are synchronous to *RD_CLK*. All status outputs are synchronous to their respective clock domains and can only be used in that clock domain. The performance of the FIFO can be measured by independently constraining the clock period for the *WR_CLK* and *RD_CLK* input signals.

The interface signals are evaluated on their rising clock edge (*WR_CLK* and *RD_CLK*). They can be made falling-edge active (relative to the clock source) by inserting an inverter between the clock source and the FIFO clock inputs. This inverter is absorbed into the internal FIFO control logic and does not cause a decrease in performance or increase in logic utilization.

Initializing the FIFO Generator

When designing with the built-in FIFO or common clock shift register FIFO, the FIFO must be reset after the FPGA is configured and before operation begins. An asynchronous reset pin (*RST*) is provided, which is an asynchronous reset that clears the internal counters and output registers.

For FIFOs implemented with block RAM or distributed RAM, a reset is not required, and the input pin is optional. For common clock configurations, users have the option of asynchronous or synchronous reset. For independent clock configurations, only asynchronous reset is available.

When asynchronous reset is implemented, it is synchronized to the clock domain in which it is used to ensure that the FIFO initializes to a known state. This synchronization logic allows for proper reset timing of the core logic, avoiding glitches and metastable behavior. The reset pulse and synchronization delay requirements are dependent on the FIFO implementation types. See “Reset Behavior,” page 71.

FIFO Implementations

Each FIFO configuration has a set of allowable features, as defined in Table 2-3, page 20.

Independent Clocks: Block RAM and Distributed RAM

Figure 4-2 illustrates the functional implementation of a FIFO configured with independent clocks. This implementation uses block RAM or distributed RAM for memory, counters for write and read pointers, conversions between binary and Gray code for synchronization across clock domains, and logic for calculating the status flags.




Figure 4-2: Functional Implementation of a FIFO with Independent Clock Domains

This FIFO is designed to support an independent read clock (RD_CLK) and write clock (WR_CLK); in other words, there is no required relationship between RD_CLK and WR_CLK with regard to frequency or phase. [Table 4-1](#) summarizes the FIFO interface signals, which are only valid in their respective clock domains.

Table 4-1: Interface Signals and Corresponding Clock Domains

WR_CLK	RD_CLK
DIN	DOUT
WR_EN	RD_EN
FULL	EMPTY
ALMOST_FULL	ALMOST_EMPTY
PROG_FULL	PROG_EMPTY
WR_ACK	VALID
OVERFLOW	UNDERFLOW
WR_DATA_COUNT	RD_DATA_COUNT
	SBITERR
	DBITERR

For FIFO cores using independent clocks, the timing relationship between the write and read operations and the status flags is affected by the relationship of the two clocks. For example, the timing between writing to an empty FIFO and the deassertion of EMPTY is determined by the phase and frequency relationship between the write and read clocks. For additional information refer to the [“Synchronization Considerations,”](#) page 43.

Independent Clocks: Built-in FIFO

[Figure 4-3](#) illustrates the functional implementation of FIFO configured with independent clocks using the Virtex-5 FPGA built-in FIFO primitive. This design implementation consists of cascaded built-in FIFO primitives and handshaking logic. The number of built-in primitives depends on the FIFO width and depth requested.

The Virtex-4 FPGA built-in FIFO implementation allows generation of a single primitive. The generated core includes a FIFO flag patch (defined in "Solution 1: Synchronous/Asynchronous Clock Work-Arounds," in the *Virtex-4 FPGA User Guide*).




Figure 4-3: Functional Implementation of Built-in FIFO

This FIFO is designed to support an independent read clock (RD_CLK) and write clock (WR_CLK); in other words, there is no required relationship between RD_CLK and WR_CLK with regard to frequency or phase. Table 4-2 summarizes the FIFO interface signals, which are only valid in their respective clock domains.

Table 4-2: Interface Signals and Corresponding Clock Domains

WR_CLK	RD_CLK
DIN	DOUT
WR_EN	RD_EN
FULL	EMPTY
PROG_FULL	PROG_EMPTY
WR_ACK	VALID
OVERFLOW	UNDERFLOW
	SBITERR
	DBITERR

For FIFO cores using independent clocks, the timing relationship between the write and read operations and the status flags is affected by the relationship of the two clocks. For example, the timing between writing to an empty FIFO and the deassertion of EMPTY is determined by the phase and frequency relationship between the write and read clocks. For additional information, see “Synchronization Considerations,” page 43.

For Virtex-5 FPGA built-in FIFO configuration, the built-in ECC feature in the FIFO macro is provided. For more information, see “Built-in Error Correction Checking,” page 70.

Common Clock: Built-in FIFO

The FIFO Generator supports FIFO cores using the built-in FIFO primitive with a common clock. This provides users the ability to use the built-in FIFO, while requiring only a single clock interface. The behavior of the common clock configuration with built-in FIFO is

identical to the independent clock configuration with built-in FIFO, except all operations are in relation to the common clock (CLK). See “Independent Clocks: Built-in FIFO,” page 46, for more information.

Common Clock FIFO: Block RAM and Distributed RAM

Figure 4-4 illustrates the functional implementation of a FIFO configured with a common clock using block RAM or distributed RAM for memory. All signals are synchronous to a single clock input (CLK). This design implements counters for write and read pointers and logic for calculating the status flags. An optional synchronous (SRST) or asynchronous (RST) reset signal is also available.




Figure 4-4: Functional Implementation of a Common Clock FIFO using Block RAM or Distributed RAM

Common Clock FIFO: Shift Registers

Figure 4-5 illustrates the functional implementation of a FIFO configured with a common clock using shift registers for memory. All operations are synchronous to the same clock

input (CLK). This design implements a single up/down counter for both the write and read pointers and logic for calculating the status flags.




Figure 4-5: Functional Implementation of a Common Clock FIFO using Shift Registers

FIFO Usage and Control

Write Operation

This section describes the behavior of a FIFO write operation and the associated status flags. When write enable is asserted and the FIFO is not full, data is added to the FIFO from the input bus (DIN) and write acknowledge (WR_ACK) is asserted. If the FIFO is continuously written to without being read, it fills with data. Write operations are only successful when the FIFO is not full. When the FIFO is full and a write is initiated, the request is ignored, the overflow flag is asserted and there is no change in the state of the FIFO (overflowing the FIFO is non-destructive).

ALMOST_FULL and FULL Flags

Note: The Built-in FIFO for Virtex-5 and Virtex-4 FPGAs do not support the ALMOST_FULL flag.

The almost full flag (ALMOST_FULL) indicates that only one more write can be performed before FULL is asserted. This flag is active high and synchronous to the write clock (WR_CLK).

The full flag (FULL) indicates that the FIFO is full and no more writes can be performed until data is read out. This flag is active high and synchronous to the write clock (WR_CLK). If a write is initiated when FULL is asserted, the write request is ignored and OVERFLOW is asserted.

Important: For the Virtex-4 FPGA built-in FIFO implementation, the Full signal has an extra cycle of latency. Use Write Acknowledge to verify success or Programmable Full for an earlier indication.

Example Operation

Figure 4-6 shows a typical write operation. The user asserts WR_EN, causing a write operation to occur on the next rising edge of the WR_CLK. Because the FIFO is not full, WR_ACK is asserted, acknowledging a successful write operation. When only one additional word can be written into the FIFO, the FIFO asserts the ALMOST_FULL flag. When ALMOST_FULL is asserted, one additional write causes the FIFO to assert FULL. When a write occurs after FULL is asserted, WR_ACK is deasserted and OVERFLOW is asserted, indicating an overflow condition. Once the user performs one or more read operations, the FIFO deasserts FULL, and data can successfully be written to the FIFO, as is indicated by the assertion of WR_ACK and deassertion of OVERFLOW.

Note: The Virtex-4 FPGA built-in FIFO implementation shows an extra cycle of latency on the FULL flag.




Figure 4-6: Write Operation for a FIFO with Independent Clocks

Read Operation

This section describes the behavior of a FIFO read operation and the associated status flags. When read enable is asserted and the FIFO is not empty, data is read from the FIFO on the output bus (DOUT), and the valid flag (VALID) is asserted. If the FIFO is continuously read without being written, the FIFO empties. Read operations are successful when the FIFO is not empty. When the FIFO is empty and a read is requested, the read operation is ignored, the underflow flag is asserted and there is no change in the state of the FIFO (underflowing the FIFO is non-destructive).

ALMOST_EMPTY and EMPTY Flags

Note: The Virtex-5 and Virtex-4 FPGAs built-in FIFO does not support the ALMOST_EMPTY flag.

The almost empty flag (ALMOST_EMPTY) indicates that the FIFO will be empty after one more read operation. This flag is active high and synchronous to RD_CLK. This flag is asserted when the FIFO has one remaining word that can be read.

The empty flag (EMPTY) indicates that the FIFO is empty and no more reads can be performed until data is written into the FIFO. This flag is active high and synchronous to

the read clock (RD_CLK). If a read is initiated when EMPTY is asserted, the request is ignored and UNDERFLOW is asserted.

Common Clock Note

When write and read operations occur simultaneously while EMPTY is asserted, the write operation is accepted and the read operation is ignored. On the next clock cycle, EMPTY is deasserted and UNDERFLOW is asserted.

Modes of Read Operation

The FIFO Generator supports two modes of read operations, standard read operation and first-word fall-through (FWFT) read operation. The standard read operation provides the user data on the cycle after it was requested. The FWFT read operation provides the user data on the same cycle in which it is requested.

Table 4-3 details the supported implementations for FWFT.

Table 4-3: Implementation-Specific Support for First-Word Fall-Through

FIFO Implementation		FWFT Support
Independent Clocks	block RAM	✓
	Distributed RAM	✓
	Built-in	✓ ¹
Common Clock	block RAM	✓
	Distributed RAM	✓✓
	Shift Register	
	Built-in	✓ ¹

1. Only supported in Virtex-5 FPGAs.

Standard FIFO Read Operation

For a standard FIFO read operation, after read enable is asserted and if the FIFO is not empty, the next data stored in the FIFO is driven on the output bus (DOUT) and the valid flag (VALID) is asserted.

Figure 4-7 shows a standard read access. Once the user writes at least one word into the FIFO, EMPTY is deasserted—indicating data is available to be read. The user asserts RD_EN, causing a read operation to occur on the next rising edge of RD_CLK. The FIFO outputs the next available word on DOUT and asserts VALID, indicating a successful read operation. When the last data word is read from the FIFO, the FIFO asserts EMPTY. If the user continues to assert RD_EN while EMPTY is asserted, the read request is ignored, VALID is deasserted, and UNDERFLOW is asserted. Once the user performs a write operation, the FIFO deasserts EMPTY, allowing the user to resume valid read operations, as indicated by the assertion of VALID and deassertion of UNDERFLOW.




Figure 4-7: Standard Read Operation for a FIFO with Independent Clocks

First-Word-Fall-Through FIFO Read Operation

The first-word-fall-through (FWFT) feature provides the ability to look-ahead to the next word available from the FIFO without issuing a read operation. When data is available in the FIFO, the first word falls through the FIFO and appears automatically on the output bus (DOUT). Once the first word appears on DOUT, EMPTY is deasserted indicating one or more readable words in the FIFO, and VALID is asserted, indicating a valid word is present on DOUT.

Figure 4-8 shows a FWFT read access. Initially, the FIFO is not empty, the next available data word is placed on the output bus (DOUT), and VALID is asserted. When the user asserts RD_EN, the next rising clock edge of RD_CLK places the next data word onto DOUT. After the last data word has been placed on DOUT, an additional read request by the user causes the data on DOUT to become invalid, as indicated by the deassertion of VALID and the assertion of EMPTY. Any further attempts to read from the FIFO results in an underflow condition.

Unlike the standard read mode, the first-word-fall-through empty flag is asserted after the last data is read from the FIFO. When EMPTY is asserted, VALID is deasserted. In the standard read mode, when EMPTY is asserted, VALID is asserted for 1 clock cycle. The FWFT feature also increases the effective read depth of the FIFO by two read words.

The FWFT feature adds two clock cycle latency to the deassertion of empty, when the first data is written into a empty FIFO.

Note: For every write operation, an equal number of read operations is required to empty the FIFO—this is true for both the first-word-fall-through and standard FIFO.




Figure 4-8: FWFT Read Operation for a FIFO with Independent Clocks

Common Clock FIFO, Simultaneous Read and Write Operation

Figure 4-9 shows a typical write and read operation. A write is issued to the FIFO, resulting in the deassertion of the `EMPTY` flag. A simultaneous write and read is then issued, resulting in no change in the status flags. Once two or more words are present in the FIFO, the `ALMOST_EMPTY` flag is deasserted. Write requests are then issued to the FIFO, resulting in the assertion of `ALMOST_FULL` when the FIFO can only accept one more write (without a read). A simultaneous write and read is then issued, resulting in no change in the status flags. Finally one additional write without a read results in the FIFO asserting `FULL`, indicating no further data can be written until a read request is issued.




Figure 4-9: Write and Read Operation for a FIFO with Common Clocks

Handshaking Flags

Handshaking flags (valid, underflow, write acknowledge and overflow) are supported to provide additional information regarding the status of the write and read operations. The handshaking flags are optional, and can be configured as active high or active low through the CORE Generator GUI (see Handshaking Options in Chapter 4 for more information). These flags (configured as active high) are illustrated in Figure 4-10.

Write Acknowledge

The write acknowledge flag (`WR_ACK`) is asserted at the completion of each successful write operation and indicates that the data on the `DIN` port has been stored in the FIFO. This flag is synchronous to the write clock (`WR_CLK`).

Valid

The operation of the valid flag (`VALID`) is dependent on the read mode of the FIFO. This flag is synchronous to the read clock (`RD_CLK`).

Standard FIFO Read Operation

For standard read operation, the `VALID` flag is asserted at the rising edge of `RD_CLK` for each successful read operation, and indicates that the data on the `DOOUT` bus is valid. When a read request is unsuccessful (when the FIFO is empty), `VALID` is not asserted.

FWFT FIFO Read Operation

For FWFT read operation, the `VALID` flag indicates the data on the output bus (`DOOUT`) is valid for the current cycle. A read request does not have to happen for data to be present and valid, as the first-word fall-through logic automatically places the next data to be read

on the DOUT bus. `VALID` is asserted if there is one or more words in the FIFO. `VALID` is deasserted when there are no more words in the FIFO.

Example Operation

[Figure 4-10](#) illustrates the behavior of the FIFO flags. On the write interface, `FULL` is not asserted and writes to the FIFO are successful (as indicated by the assertion of `WR_ACK`). When a write occurs after `FULL` is asserted, `WR_ACK` is deasserted and `OVERFLOW` is asserted, indicating an overflow condition. On the read interface, once the FIFO is not `EMPTY`, the FIFO accepts read requests. In standard FIFO operation, `VALID` is asserted and `DOUT` is updated on the clock cycle following the read request. In FWFT operation, `VALID` is asserted and `DOUT` is updated prior to a read request being issued. When a read request is issued while `EMPTY` is asserted, `VALID` is deasserted and `UNDERFLOW` is asserted, indicating an underflow condition.




Figure 4-10: Handshaking Signals for a FIFO with Independent Clocks

Underflow

The underflow flag (UNDERFLOW) is used to indicate that a read operation is unsuccessful. This occurs when a read is initiated and the FIFO is empty. This flag is synchronous with the read clock (RD_CLK). Underflowing the FIFO does not change the state of the FIFO (it is non-destructive).

Overflow

The overflow flag (`OVERFLOW`) is used to indicate that a write operation is unsuccessful. This flag is asserted when a write is initiated to the FIFO while `FULL` is asserted. The overflow flag is synchronous to the write clock (`WR_CLK`). Overflowing the FIFO does not change the state of the FIFO (it is non-destructive).

Example Operation

Figure 4-11 illustrates the Handshaking flags. On the write interface, `FULL` is deasserted and therefore writes to the FIFO are successful (indicated by the assertion of `WR_ACK`). When a write occurs after `FULL` is asserted, `WR_ACK` is deasserted and `OVERFLOW` is asserted, indicating an overflow condition. On the read interface, once the FIFO is not `EMPTY`, the FIFO accepts read requests. Following a read request, `VALID` is asserted and `DOUT` is updated. When a read request is issued while `EMPTY` is asserted, `VALID` is deasserted and `UNDERFLOW` is asserted, indicating an underflow condition.




Figure 4-11: Handshaking Signals for a FIFO with Common Clocks

Programmable Flags

The FIFO supports programmable flags to indicate that the FIFO has reached a user-defined fill level.

- Programmable full (`PROG_FULL`) indicates that the FIFO has reached a user-defined full threshold.
- Programmable empty (`PROG_EMPTY`) indicates that the FIFO has reached a user-defined empty threshold.

For these thresholds, the user can set a constant value or choose to have dedicated input ports, enabling the thresholds to change dynamically in circuit. Hysteresis is also

optionally supported, by providing unique assert and negate values for each flag. Detailed information about these options are provided below. For information about the latency behavior of the programmable flags, see “Latency,” page 78.

Programmable Full

The FIFO Generator supports four ways to define the programmable full threshold:

- Single threshold constant
- Single threshold with dedicated input port
- Assert and negate threshold constants (provides hysteresis)
- Assert and negate thresholds with dedicated input ports (provides hysteresis)

Note: The built-in FIFOs only support single-threshold constant programmable full.

These options are available in the CORE Generator GUI and accessed within the programmable flags window (Figure 3-4).

The programmable full flag (`PROG_FULL`) is asserted when the number of entries in the FIFO is greater than or equal to the user-defined assert threshold. When the programmable full flag is asserted, the FIFO can continue to be written to until the full flag (`FULL`) is asserted. If the number of words in the FIFO is less than the negate threshold, the flag is deasserted.

Note: If a write operation occurs on a rising clock edge that causes the number of words to meet or exceed the programmable full threshold, then the programmable full flag will assert on the next rising clock edge. The deassertion of the programmable full flag has a longer delay, and depends on the relationship between the write and read clocks.

Programmable Full: Single Threshold

This option enables the user to set a single threshold value for the assertion and deassertion of `PROG_FULL`. When the number of entries in the FIFO is greater than or equal to the threshold value, `PROG_FULL` is asserted. The deassertion behavior differs between built-in and non built-in FIFOs (Block RAM, Distributed RAM, and so forth).

For built-in FIFOs, the number of entries in the FIFO has to be less than the threshold value -1 before `PROG_FULL` is deasserted. For non built-in FIFOs, if the number of words in the FIFO is less than the negate threshold, the flag is deasserted.

Two options are available to implement this threshold:

- **Single threshold constant.** User specifies the threshold value through the CORE Generator GUI. Once the core is generated, this value can only be changed by re-generating the core. This option consumes fewer resources than the single threshold with dedicated input port.
- **Single threshold with dedicated input port** (non-built-in FIFOs only). User specifies the threshold value through an input port (`PROG_FULL_THRESH`) on the core. This input can be changed while the FIFO is in reset, providing the user the flexibility to change the programmable full threshold in-circuit without re-generating the core.

Note: See the CORE Generator GUI screen for valid ranges for each threshold.

Figure 4-12 shows the programmable full flag with a single threshold for a non-built-in FIFO. The user writes to the FIFO until there are seven words in the FIFO. Because the programmable full threshold is set to seven, the FIFO asserts `PROG_FULL` once seven words are written into the FIFO. Note that both write data count (`WR_DATA_COUNT`) and `PROG_FULL` have one clock cycle of delay. Once the FIFO has six or fewer words in the FIFO, `PROG_FULL` is deasserted.




Figure 4-12: Programmable Full Single Threshold: Threshold Set to 7

Programmable Full: Assert and Negate Thresholds

This option enables the user to set separate values for the assertion and deassertion of `PROG_FULL`. When the number of entries in the FIFO is greater than or equal to the assert value, `PROG_FULL` is asserted. When the number of entries in the FIFO is less than the negate value, `PROG_FULL` is deasserted. Note that this feature is not available for built-in FIFOs.

Two options are available to implement these thresholds:

- Assert and negate threshold constants: User specifies the threshold values through the CORE Generator GUI. Once the core is generated, these values can only be changed by re-generating the core. This option consumes fewer resources than the assert and negate thresholds with dedicated input ports.
- Assert and negate thresholds with dedicated input ports: User specifies the threshold values through input ports on the core. These input ports can be changed while the FIFO is in reset, providing the user the flexibility to change the values of the programmable full assert (`PROG_FULL_THRESH_ASSERT`) and negate (`PROG_FULL_THRESH_NEGATE`) thresholds in-circuit without re-generating the core.

Note: The full assert value must be larger than the full negate value. Refer to the CORE Generator GUI for valid ranges for each threshold.

Figure 4-13 shows the programmable full flag with assert and negate thresholds. The user writes to the FIFO until there are 10 words in the FIFO. Because the assert threshold is set to 10, the FIFO then asserts `PROG_FULL`. The negate threshold is set to seven, and the FIFO deasserts `PROG_FULL` once six words or fewer are in the FIFO. Both write data count (`WR_DATA_COUNT`) and `PROG_FULL` have one clock cycle of delay.




Figure 4-13: Programmable Full with Assert and Negate Thresholds: Assert Set to 10 and Negate Set to 7

Programmable Full Threshold Range Restrictions

The programmable full threshold ranges depend on several features that dictate the way the FIFO is implemented, and include the following features:

- FIFO Implementation Type (Built-in FIFO or non Built-in FIFO, Common or Independent Clock FIFOs, and so forth)
- Symmetric or Non-symmetric Port Aspect Ratio
- Read Mode (Standard or First-Word-Fall-Through)
- Read and Write Clock Frequencies (Virtex-4 FPGA, Built-in FIFOs only)

The FIFO Generator GUI automatically parameterizes the threshold ranges based on these features, allowing you to choose only within the valid ranges. Note that for the Common or Independent Clock Built-in FIFO implementation type, you can only choose a threshold range within 1 primitive deep of the FIFO depth, due to the core implementation. If a wider threshold range is required, use the Common or Independent Clock Block RAM implementation type.

Programmable Empty

The FIFO Generator supports four ways to define the programmable empty thresholds:

- Single threshold constant
- Single threshold with dedicated input port
- Assert and negate threshold constants (provides hysteresis)
- Assert and negate thresholds with dedicated input ports (provides hysteresis)

Note: The built-in FIFOs only support single-threshold constant programmable full.

These options are available in the CORE Generator GUI and accessed within the programmable flags window (Figure 3-4).

The programmable empty flag (PROG_EMPTY) is asserted when the number of entries in the FIFO is less than or equal to the user-defined assert threshold. If the number of words in the FIFO is greater than the negate threshold, the flag is deasserted.

Note: If a read operation occurs on a rising clock edge that causes the number of words in the FIFO to be equal to or less than the programmable empty threshold, then the programmable empty flag will assert on the next rising clock edge. The deassertion of the programmable empty flag has a longer delay, and depends on the read and write clocks.

Programmable Empty: Single Threshold

This option enables you to set a single threshold value for the assertion and deassertion of `PROG_EMPTY`. When the number of entries in the FIFO is less than or equal to the threshold value, `PROG_EMPTY` is asserted. The deassertion behavior differs between built-in and non built-in FIFOs (Block RAM, Distributed RAM, and so forth).

For built-in FIFOs, the number of entries in the FIFO must be greater than the threshold value + 1 before `PROG_EMPTY` is deasserted. For non built-in FIFOs, if the number of entries in the FIFO is greater than threshold value, `PROG_EMPTY` is deasserted.

Two options are available to implement this threshold:

- **Single threshold constant:** User specifies the threshold value through the CORE Generator GUI. Once the core is generated, this value can only be changed by re-generating the core. This option consumes fewer resources than the single threshold with dedicated input port.
- **Single threshold with dedicated input port:** User specifies the threshold value through an input port (`PROG_EMPTY_THRESH`) on the core. This input can be changed while the FIFO is in reset, providing the flexibility to change the programmable empty threshold in-circuit without re-generating the core.

Note: See the CORE Generator GUI for valid ranges for each threshold.

Figure 4-14 shows the programmable empty flag with a single threshold for a non-built-in FIFO. The user writes to the FIFO until there are five words in the FIFO. Because the programmable empty threshold is set to four, `PROG_EMPTY` is asserted until more than four words are present in the FIFO. Once five words (or more) are present in the FIFO, `PROG_EMPTY` is deasserted. Both read data count (`RD_DATA_COUNT`) and `PROG_EMPTY` have one clock cycle of delay.




Figure 4-14: Programmable Empty with Single Threshold: Threshold Set to 4

Programmable Empty: Assert and Negate Thresholds

This option lets the user set separate values for the assertion and deassertion of `PROG_EMPTY`. When the number of entries in the FIFO is less than or equal to the assert value, `PROG_EMPTY` is asserted. When the number of entries in the FIFO is greater than the negate value, `PROG_EMPTY` is deasserted. This feature is not available for built-in FIFOs.

Two options are available to implement these thresholds.

- **Assert and negate threshold constants.** The threshold values are specified through the CORE Generator GUI. Once the core is generated, these values can only be changed by re-generating the core. This option consumes fewer resources than the assert and negate thresholds with dedicated input ports.

- **Assert and negate thresholds with dedicated input ports.** The threshold values are specified through input ports on the core. These input ports can be changed while the FIFO is in reset, providing the user the flexibility to change the values of the programmable empty assert (`PROG_EMPTY_THRESH_ASSERT`) and negate (`PROG_EMPTY_THRESH_NEGATE`) thresholds in-circuit without regenerating the core.

Note: The empty assert value must be less than the empty negate value. Refer to the CORE Generator GUI for valid ranges for each threshold.

Figure 4-15 shows the programmable empty flag with assert and negate thresholds. The user writes to the FIFO until there are eleven words in the FIFO; because the programmable empty deassert value is set to ten, `PROG_EMPTY` is deasserted when more than ten words are in the FIFO. Once the FIFO contains less than or equal to the programmable empty negate value (set to seven), `PROG_EMPTY` is asserted. Both read data count (`RD_DATA_COUNT`) and `PROG_EMPTY` have one clock cycle of delay.




Figure 4-15: Programmable Empty with Assert and Negate Thresholds: Assert Set to 7 and Negate Set to 10

Programmable Empty Threshold Range Restrictions

The programmable empty threshold ranges depend on several features that dictate the way the FIFO is implemented, including the following:

- FIFO Implementation Type (Built-in FIFO or non Built-in FIFO, Common or Independent Clock FIFOs, and so forth)
- Symmetric or Non-symmetric Port Aspect Ratio
- Read Mode (Standard or First-Word-Fall-Through)
- Read and Write Clock Frequencies (Virtex-4 FPGA Built-in FIFOs only)

The FIFO Generator GUI automatically parameterizes the threshold ranges based on these features, allowing you to choose only within the valid ranges. Note that for Common or Independent Clock Built-in FIFO implementation type, you can only choose a threshold range within 1 primitive deep of the FIFO depth due to the core implementation. If a wider threshold range is needed, use the Common or Independent Clock Block RAM implementation type.

Data Counts

`DATA_COUNT` tracks the number of words in the FIFO. You can specify the width of the data count bus with a maximum width of \log_2 (FIFO depth). If the width specified is smaller than the maximum allowable width, the bus is truncated by removing the lower bits. These signals are optional outputs of the FIFO Generator, and are enabled through the CORE Generator GUI. Table 4-4 identifies data count support for each FIFO implementation. For information about the latency behavior of data count flags, see “Latency,” page 78.

Table 4-4: Implementation-specific Support for Data Counts

FIFO Implementation		Data Count Support
Independent Clocks	block RAM	✓
	Distributed RAM	✓
	Built-in	
Common Clock	block RAM	✓
	Distributed RAM	✓
	Shift Register	✓
	Built-in	

Data Count (Common Clock FIFO Only)

Data Count output (`DATA_COUNT`) accurately reports the number of words available in a Common Clock FIFO. You can specify the width of the data count bus with a maximum width of $\log_2(\text{depth})$. If the width specified is smaller than the maximum allowable width, the bus is truncated with the lower bits removed.

For example, you can specify to use two bits out of a maximum allowable three bits (provided a FIFO depth of eight). These two bits indicate the number of words in the FIFO with a quarter resolution, providing the status of the contents of the FIFO for read and write operations.

Note: If a read or write operation occurs on a rising edge of `CLK`, the data count port is updated at the same rising edge of `CLK`.

Read Data Count (Independent Clock FIFO Only)

Read data count (`RD_DATA_COUNT`) pessimistically reports the number of words available for reading. The count is guaranteed to never over-report the number of words available in the FIFO (although it may temporarily under-report the number of words available) to ensure that the user design never underflows the FIFO. The user can specify the width of the read data count bus with a maximum width of $\log_2(\text{read depth})$. If the width specified is smaller than the maximum allowable width, the bus is truncated with the lower bits removed.

For example, the user can specify to use two bits out of a maximum allowable three bits (provided a FIFO depth of eight). These two bits indicate the number of words in the FIFO, with a quarter resolution. This provides a status of the contents of the FIFO for the read clock domain.

Note: If a read operation occurs on a rising clock edge of `RD_CLK`, that read is reflected on the `RD_DATA_COUNT` signal following the next rising clock edge. A write operation on the `WR_CLK` clock domain may take a number of clock cycles before being reflected in the `RD_DATA_COUNT`.

Write Data Count (Independent Clock FIFO Only)

Write data count (`WR_DATA_COUNT`) pessimistically reports the number of words written into the FIFO. The count is guaranteed to never under-report the number of words in the FIFO (although it may temporarily over-report the number of words present) to ensure that the user never overflows the FIFO. The user can specify the width of the write data

count bus with a maximum width of \log_2 (write depth). If the width specified is smaller than the maximum allowable width, the bus is truncated with the lower bits removed.

For example, you can only use two bits out of a maximum allowable three bits (provided a FIFO depth of eight). These two bits indicate the number of words in the FIFO, with a quarter resolution. This provides a status of the contents of the FIFO for the write clock domain.

Note: If a write operation occurs on a rising clock edge of `WR_CLK`, that write will be reflected on the `WR_DATA_COUNT` signal following the next rising clock edge. A read operation, which occurs on the `RD_CLK` clock domain, may take a number of clock cycles before being reflected in the `WR_DATA_COUNT`.

First-Word Fall-Through Data Count

By providing the capability to read the next data word before requesting it, first-word fall-through (FWFT) implementations increase the depth of the FIFO by 2 read words. Using this configuration, the FIFO Generator enables the user to generate data count in two ways:

- Approximate Data Count
- More Accurate Data Count (Use Extra Logic)

Approximate Data Count

Approximate Data Count behavior is the default option in the CORE Generator GUI for independent clock block RAM and distributed RAM FIFOs. This feature is not available for common clock FIFOs. The width of the `WR_DATA_COUNT` and `RD_DATA_COUNT` is identical to the non first-word-fall-through configurations (\log_2 (write depth) and \log_2 (read depth), respectively) but the data counts reported is an approximation because the actual full depth of the FIFO is not supported.

Using this option, you can use specific bits in `WR_DATA_COUNT` and `RD_DATA_COUNT` to approximately indicate the status of the FIFO, for example, half full, quarter full, and so forth.

For example, for a FIFO with a depth of 16, symmetric read and write port widths, and the first-word-fall-through option selected, the *actual* FIFO depth increases from 15 to 17. When using approximate data count, the width of `WR_DATA_COUNT` and `RD_DATA_COUNT` is 4 bits, with a maximum of 15. For this option, you can use the assertion of the MSB bit of the data count to indicate that the FIFO is approximately half full.

More Accurate Data Count (Use Extra Logic)

This feature is enabled when Use Extra Logic for More Accurate Data Counts is selected in the CORE Generator GUI. In this configuration, the width of `WR_DATA_COUNT`, `RD_DATA_COUNT`, and `DATA_COUNT` is $\log_2(\text{write depth})+1$, $\log_2(\text{read depth})+1$, and $\log_2(\text{depth})+1$, respectively to accommodate the increase in depth in the first-word-fall-through case and to ensure accurate data count is provided.

Note that when using this option, you *cannot* use any one bit of `WR_DATA_COUNT`, `RD_DATA_COUNT`, and `DATA_COUNT` to indicate the status of the FIFO, for example, approximately half full, quarter full, and so forth.

For example, for an independent FIFO with a depth of 16, symmetric read and write port widths, and the first-word-fall-through option selected, the *actual* FIFO depth increases from 15 to 17. When using accurate data count, the width of the `WR_DATA_COUNT` and `RD_DATA_COUNT` is 5 bits, with a maximum of 31. For this option, you must use the

assertion of both the MSB and MSB-1 bit of the data count to indicate that the FIFO is at least half full.

Data Count Behavior

For FWFT implementations using More Accurate Data Counts (Use Extra Logic), `DATA_COUNT` is guaranteed to be accurate when words are present in the FIFO, with the exception of when its near empty or almost empty or when initial writes occur on an empty FIFO. In these scenarios, `DATA_COUNT` may be incorrect on up to two words.

[Table 4-5](#) defines the value of `DATA_COUNT` when FIFO is empty.

From the point-of-view of the write interface, `DATA_COUNT` is always accurate, reporting the first word immediately once its written to the FIFO. However, from the point-of-view of the read interface, the `DATA_COUNT` output may over-report by up to two words until `ALMOST_EMPTY` and `EMPTY` have both deasserted. This is due to the latency of `EMPTY` deassertion in the first-word-fall-through FIFO (see [Table 4-17](#)). This latency allows `DATA_COUNT` to reflect written words which may not yet be available for reading.

From the point-of-view of the read interface, the data count starts to transition from over-reporting to accurate-reporting at the deassertion to empty. This transition completes after `ALMOST_EMPTY` deasserts. Before `ALMOST_EMPTY` deasserts, the `DATA_COUNT` signal may exhibit the following atypical behaviors:

- From the read-interface perspective, `DATA_COUNT` may over-report up to two words.

Write Data Count Behavior

Even for FWFT implementations using More Accurate Data Counts (Use Extra Logic), `WR_DATA_COUNT` will still pessimistically report the number of words written into the FIFO. However, the addition of this feature will cause `WR_DATA_COUNT` to further over-report up to two read words (and 1 to 16 write words, depending on read and write port aspect ratio) when the FIFO is at or near empty or almost empty.

[Table 4-5](#) defines the value of `WR_DATA_COUNT` when the FIFO is empty.

The `WR_DATA_COUNT` starts to transition out of over-reporting two extra read words at the deassertion of `EMPTY`. This transition completes several clock cycles after `ALMOST_EMPTY` deasserts. Note that prior to the transition period, `WR_DATA_COUNT` will always over-report by at least two read words. During the transition period, the `WR_DATA_COUNT` signal may exhibit the following strange behaviors:

- `WR_DATA_COUNT` may decrement although no read operation has occurred.
- `WR_DATA_COUNT` may not increment as expected due to a write operation.

Note: During reset, `WR_DATA_COUNT` and `DATA_COUNT` value is set to 0.

Table 4-5: Empty FIFO `WR_DATA_COUNT`/`DATA_COUNT` Value

Write Depth to Read Depth Ratio	Approximate <code>WR_DATA_COUNT</code>	More Accurate <code>WR_DATA_COUNT</code>	More Accurate <code>DATA_COUNT</code>
1:1	0	2	2
1:2	0	1	N/A
1:4	0	0	N/A
1:8	0	0	N/A
2:1	0	4	N/A

Table 4-5: Empty FIFO WR_DATA_COUNT/DATA_COUNT Value

4:1	0	8	N/A
8:1	0	16	N/A

Example Operation

Figure 4-16 shows write and read data counts. When WR_EN is asserted and FULL is deasserted, WR_DATA_COUNT increments. Similarly, when RD_EN is asserted and EMPTY is deasserted, RD_DATA_COUNT decrements.

Note: In the first part of Figure 4-16, a successful write operation occurs on the third rising clock edge, and is not reflected on WR_DATA_COUNT until the next full clock cycle is complete. Similarly, RD_DATA_COUNT transitions one full clock cycle after a successful read operation.




Figure 4-16: Write and Read Data Counts for FIFO with Independent Clocks

Non-symmetric Aspect Ratios

Table 4-6 identifies support for non-symmetric aspect ratios.

Table 4-6: Implementation-specific Support for Non-symmetric Aspect Ratios

FIFO Implementation		Non-symmetric Aspect Ratios Support
Independent Clocks	block RAM	✓
	Distributed RAM	
	Built-in	

Table 4-6: Implementation-specific Support for Non-symmetric Aspect Ratios

FIFO Implementation		Non-symmetric Aspect Ratios Support
Common Clock	block RAM	
	Distributed RAM	
	Shift Register	
	Built-in	

This feature is supported for FIFOs configured with independent clocks implemented with block RAM. Non-symmetric aspect ratios allow the input and output depths of the FIFO to be different. The following write-to-read aspect ratios are supported: 1:8, 1:4, 1:2, 1:1, 2:1, 4:1, 8:1. This feature is enabled by selecting unique write and read widths when customizing the FIFO using the CORE Generator. By default, the write and read widths are set to the same value (providing a 1:1 aspect ratio); but any ratio between 1:8 to 8:1 is supported, and the output depth of the FIFO is automatically calculated from the input depth and the write and read widths.

For non-symmetric aspect ratios, the full and empty flags are active only when one complete word can be written or read. The FIFO does not allow partial words to be accessed. For example, assuming a full FIFO, if the write width is 8 bits and read width is 2 bits, the user would have to complete four valid read operations before full deasserts and a write operation accepted. Write data count shows the number of FIFO words according to the write port ratio, and read data count shows the number of FIFO words according to the read port ratio.

Note: For non-symmetric aspect ratios where the write width is smaller than the read width (1:8, 1:4, 1:2), the most significant bits are read first (refer to Figure 4-17 and Figure 4-18).

Figure 4-17 is an example of a FIFO with a 1:4 aspect ratio (write width = 2, read width = 8). In this figure, four consecutive write operations are performed before a read operation can be performed. The first write operation is 10, followed by 11, 00, and finally 01. The memory is filling up from the right to the left (LSB to MSB). When a read operation is performed, the received data is 01_00_11_10.




Figure 4-17: 1:4 Aspect Ratio: Data Ordering

Figure 4-18 shows DIN, DOUT and the handshaking signals for a FIFO with a 1:4 aspect ratio. After four words are written into the FIFO, EMPTY is deasserted. Then after a single read operation, EMPTY is asserted again.




Figure 4-18: 1:4 Aspect Ratio: Status Flag Behavior

Figure 4-19 shows a FIFO with an aspect ratio of 4:1 (write width of 8, read width of 2). In this example, a single write operation is performed, after which four read operations are executed. The write operation is 11_00_01_11. When a read operation is performed, the data is received left to right (MSB to LSB). As shown, the first read results in data of 11, followed by 00, 01, and then 11.




Figure 4-19: 4:1 Aspect Ratio: Data Ordering

Figure 4-20 shows DIN, DOUT, and the handshaking signals for a FIFO with an aspect ratio of 4:1. After a single write, the FIFO deasserts EMPTY. Because no other writes occur, the FIFO reasserts empty after four reads.




Figure 4-20: 4:1 Aspect Ratio: Status Flag Behavior

Non-symmetric Aspect Ratio and First-Word Fall-Through

A FWFT FIFO has 2 extra read words available on the read port when compared to a standard FIFO. For write-to-read aspect ratios that are larger or equal to 1 (1:1, 2:1, 4:1, and 8:1), the FWFT implementation also increases the number of words that can be written into the FIFO by $\text{depth_ratio} * 2$ ($\text{depth_ratio} = \text{write depth} / \text{read depth}$). For write-to-read aspect ratios smaller than 1 (1:2, 1:4 and 1:8), the addition of 2 extra read words only amounts to a fraction of 1 write word. The creation of these partial words causes the behavior of the PROG_EMPTY and WR_DATA_COUNT signals of the FIFO to differ in behavior than as previously described.

Programmable Empty

In general, PROG_EMPTY is guaranteed to assert when the number of readable words in the FIFO is less than or equal to the programmable empty assert threshold. However, when the write-to-read aspect ratios are smaller than 1 (depending on the read and write clock frequency) it is possible for PROG_EMPTY to violate this rule, but only while EMPTY is asserted. To avoid this condition, the user should set the programmable empty assert threshold to $3 * \text{depth_ratio} * \text{frequency_ratio}$ ($\text{depth_ratio} = \text{write depth} / \text{read depth}$ and $\text{frequency_ratio} = \text{write clock frequency} / \text{read clock frequency}$). If the programmable empty assert threshold is set lower than this value, the user should assume that PROG_EMPTY may or can be asserted when EMPTY is asserted.

Write Data Count

In general, WR_DATA_COUNT pessimistically reports the number of words written into the FIFO and is guaranteed to never under-report the number of words in the FIFO, to ensure that the user never overflows the FIFO. However, when the write-to-read aspect ratios are smaller than 1, if the read and write operations result in partial write words existing in the FIFO, it is possible to under-report the number of words in the FIFO. This behavior is most crucial when the FIFO is 1 or 2 words away from full, because in this state the WR_DATA_COUNT is under-reporting and cannot be used to gauge if the FIFO is full. In this configuration, you should use the FULL flag to gate any write operation to the FIFO.

Embedded Registers in block RAM and FIFO Macros (Virtex-4 and Virtex-5 FPGAs)

In Virtex-4 and Virtex-5 FPGA block RAM and FIFO macros, embedded output registers are available to increase performance and add a pipeline register to the macros. Depending on the configuration, this feature can be leveraged to add one additional latency to the FIFO core (DOUT bus and VALID outputs) or implement the output registers for FWFT FIFOs. For built-in FIFOs configuration, this feature is only available for common clock FIFOs.

Standard FIFOs

When using the embedded registers to add an output pipeline register to the standard FIFOs, only the DOUT and VALID output ports are delayed by 1 clock cycle during a read operation. These additional pipeline registers are always enabled and the DOUT reset value feature is not supported, as illustrated in [Figure 4-21](#).




Figure 4-21: Standard Read Operation for a block RAM or built-in FIFO with Use Embedded Registers Enabled

Block RAM Based FWFT FIFOs

When using the embedded output registers to implement the FWFT FIFOs, the DOUT reset value is not supported. With this exception, the behavior of the core is identical to the implementation without the embedded registers.

Built-in Based FWFT FIFOs (Common Clock Only)

When using the embedded output registers with a common clock built-in based FIFO with FWFT, the embedded registers add an output pipeline register to the FWFT FIFO. The DOUT and VALID output ports are delayed by 1 clock cycle during a read operation. These pipeline registers are always enabled and the DOUT reset value feature is not supported, as illustrated in [Figure 4-22](#). For this configuration, the embedded output register feature is only available for FIFOs that use only 1 FIFO macro in depth.




Figure 4-22: FWFT Read Operation for a Synchronous Built-in FIFO with User Embedded Registers Enabled

Note: Virtex-5 FPGA built-in FIFOs with independent clocks and FWFT always use the embedded output registers in the macro to implement the FWFT registers.

Built-in Error Correction Checking

Built-in ECC is supported for FIFOs configured with independent or common clock block RAM and built-in FIFOs targeting Virtex-5 FPGA. When ECC is enabled, the block RAM and built-in FIFO primitive used to create the FIFO is configured in the full ECC mode (both encoder and decoder enabled), providing two additional outputs to the FIFO Generator core: SBITERR and DBITERR. These outputs indicate three possible read results: no error, single error corrected, and double error detected. In the full ECC mode, the read operation does not correct the single error in the memory array, it only presents corrected data on DOUT.

Figure 4-23 shows how the SBITERR and DBITERR outputs are generated in the FIFO Generator core. The output signals are created by combining all the SBITERR and DBITERR signals from the FIFO or block RAM primitives using an OR gate. Because the FIFO primitives may be cascaded in depth, when SBITERR or DBITERR is asserted, the error may have occurred in any of the built-in FIFO macros chained in depth or block RAM macros. For this reason, these flags are not correlated to the data currently being read from the FIFO Generator core or to a read operation. For this reason, when the DBITERR is flagged, the user should assume that the data in the entire FIFO has been corrupted and the user logic needs to take the appropriate action. As an example, when DBITERR is flagged, an appropriate action for the user logic is to halt all FIFO operation, reset the FIFO, and restart the data transfer.

The SBITERR and DBITERR outputs are not registered and are generated combinatorially. If the configured FIFO uses two independent read and write clocks, the SBITERR and DBITERR outputs may be generated from either the write or read clock domain. The signals generated in the write clock domain are synchronized before being combined with the SBITERR and DBITERR signals generated in the read clock domain.

Note that due to the differing read and write clock frequencies and the OR gate used to combine the signals, the number of read clock cycles that the SBITERR and DBITERR flags assert is not an accurate indicator of the number of errors found in the built-in FIFOs.




Figure 4-23: SBITERR and DBITERR Outputs in the FIFO Generator Core

Reset Behavior

The FIFO Generator provides a single reset input that resets all counters, output registers, and memories when asserted. For block RAM or distributed RAM implementations, resetting the FIFO is not required, and the reset pin can be disabled in the FIFO. There are two reset options: asynchronous and synchronous.

Asynchronous Reset

The asynchronous reset (*RST*) input asynchronously resets all counters, output registers, and memories when asserted. When reset is implemented, it is synchronized internally to the core with each respective clock domain for setting the internal logic of the FIFO to a known state. This synchronization logic allows for proper timing of the reset logic within the core to avoid glitches and metastable behavior.

Common/Independent Clock: block RAM, Distributed RAM, and Shift RAM FIFOs

Table 4-7 defines the values of the output ports during power-up and reset state for Block RAM, Distributed RAM and Shift RAM FIFOs. Note that the underflow signal is dependent on *RD_EN*. If *RD_EN* is asserted and the FIFO is empty, underflow is asserted. The overflow signal is dependent on *WR_EN*. If *WR_EN* is asserted and the FIFO is full, overflow is asserted.

There are two asynchronous reset behaviors available for these FIFO configurations: Full flags reset to 1 and full flags reset to 0. The reset requirements and the behavior of the FIFO is different depending on the full flags reset value chosen.

Note: The reset is edge sensitive and not level sensitive. The synchronization logic looks for the rising edge of `RST` and creates an internal reset for the core. Note that the assertion of asynchronous reset immediately causes the core to go into a predetermine reset state - this is not dependent on any clock toggling. The reset synchronization logic is used to ensure that the logic in the different clock domains comes OUT of the reset mode at the same time - this is by synchronizing the deassertion of asynchronous reset to the appropriate clock domain. By doing this glitches and metastability can be avoided. This synchronization takes 4 clock cycles (write or read) after the asynchronous reset is detected on the rising edge read and write clock respectively.

Table 4-7: FIFO Asynchronous Reset Values for block RAM, Distributed RAM, and Shift RAM FIFOs

Signal	Full Flags Reset Value of 1	Full Flags Reset Value of 0	Power-up Values
DOUT	DOUT Reset Value or 0 ¹	DOUT Reset Value or 0 ¹	Same as reset values
FULL	1 ²	0	0
ALMOST FULL	1 ²	0	0
EMPTY	1	1	1
ALMOST EMPTY	1	1	1
VALID	0 (active high) or 1 (active low)	0 (active high) or 1 (active low)	0 (active high) or 1 (active low)
WR_ACK	0 (active high) or 1 (active low)	0 (active high) or 1 (active low)	0 (active high) or 1 (active low)
PROG_FULL	1 ²	0	0
PROG_EMPTY	1	1	1
RD_DATA_COUNT	0	0	0
WR_DATA_COUNT	0	0	0

1. The ability to set DOUT to a user-defined value is not available for block RAM implementations in Virtex, Spartan-II and Spartan-IIe FPGAs. DOUT resets to 0 when this feature is unavailable.

2. When reset is asserted, the FULL flags are asserted to prevent writes to the FIFO during reset.

Full Flags Reset Value of 1

In this configuration, the FIFO requires a minimum asynchronous reset pulse of 1 write clock period (`WR_CLK/CLK`). After reset is detected on the rising clock edge of write clock, 3 write clock periods are required to complete proper reset synchronization. During this time, the `FULL`, `ALMOST_FULL`, and `PROG_FULL` flags are asserted. After the FIFO exits the reset synchronization state, these flags immediately deassert and the FIFO is ready for writing.

The `FULL` and `ALMOST_FULL` flags are asserted to ensure that no write operations occur when the FIFO core is in the reset state. After the FIFO exits the reset state and is ready for writing, the `FULL` and `ALMOST_FULL` flags deassert; this occurs approximately four clock cycles after the assertion of asynchronous reset. See [Figure 4-24](#) for example behavior. Note that the power-up values for this configuration are different from the reset state value.




Figure 4-24: **Block RAM, Distributed RAM, Shift RAM with Full Flags Reset Value of 1**

Full Flags Reset Value of 0

In this configuration, the FIFO requires a minimum asynchronous reset pulse of 1 write clock cycle to complete the proper reset synchronization. At reset, FULL and ALMOST_FULL flags are deasserted. After the FIFO exits the reset synchronization state, the FIFO is ready for writing; this occurs approximately four clock cycles after the assertion of asynchronous reset. See [Figure 4-25](#) for example behavior.




Figure 4-25: Block RAM, Distributed RAM, Shift RAM with Full Flags Reset Value of 0

Common/Independent Clock: Built-in

Table 4-7 defines the values of the output ports during power-up and reset state for Built-in FIFOs. DOUT reset value is not supported for Built-in FIFOs. The Built-In FIFOs require an asynchronous reset pulse of at least 3 read and write clock cycles. During reset, the RD_EN and WR_EN ports are required to be deasserted (no read or write operation can be performed). Assertion of reset causes the FULL and PROG_FULL flags to deassert and EMPTY and PROG_EMPTY flags to assert. After asynchronous reset is released, the core exits the reset state and is ready for writing. See Figure 4-26 for example behavior.

Note that the underflow signal is dependent on RD_EN. If RD_EN is asserted and the FIFO is empty, underflow is asserted. The overflow signal is dependent on WR_EN. If WR_EN is asserted and the FIFO is full, overflow is asserted.

Table 4-8: Asynchronous FIFO Reset Values for Built-in FIFO

Signal	Built-in FIFO Reset Values	Power-up Values
DOUT	Last read value	Content of memory at location 0
FULL	0	0
EMPTY	1	1
VALID	0 (active high) or 1 (active low)	0 (active high) or 1 (active low)
PRG_FULL	0	0
PRG_EMPTY	1	1




Figure 4-26: Built-in FIFO, Asynchronous Reset Behavior

Synchronous Reset

The synchronous reset (SRST) input is only available for the Block and Distributed RAM implementation of the common clock FIFO. It synchronously resets all counters, output registers and memories when asserted. Because the reset pin is synchronous to the input clock and there is only one clock domain in the FIFO, no additional synchronization logic is necessary. Figure 4-27 illustrates the flags following the release of SRST.




Figure 4-27: Synchronous Reset: FIFO with a Common Clock

Table 4-9 defines the values of the output ports during power-up and the reset state. DOUT reset value is supported for all architectures with the exception of Virtex and Spartan-II FPGAs. If the user does not specify a DOUT reset value, it defaults to 0. The FIFO requires a reset pulse of only 1 clock cycle. The FIFOs are available for transaction on the clock cycle after the reset is released. The power-up values for the synchronous reset are the same as the reset state.

Note that the underflow signal is dependent on RD_EN. If RD_EN is asserted and the FIFO is empty, underflow is asserted. The overflow signal is dependent on WR_EN. If WE_EN is asserted and the FIFO is full, overflow is asserted.

Table 4-9: Synchronous FIFO Reset and Power-up Values

Signal	Block Memory and Distributed Memory Values of Output Ports During Reset and Power-up
DOUT	DOUT Reset Value or 0 ¹
FULL	0
ALMOST FULL	0
EMPTY	1
ALMOST EMPTY	1
VALID	0 (active high) or 1 (active low)
WR_ACK	0 (active high) or 1 (active low)
PROG_FULL	0
PROG_EMPTY	0
RD_DATA_COUNT	0
WR_DATA_COUNT	0

1. The ability to set DOUT to a user-defined value is not available for block RAM implementations in Virtex, Spartan-II, and Spartan-III FPGAs. DOUT resets to 0 when this feature is unavailable.

Actual FIFO Depth

Of critical importance is the understanding that the *effective* or *actual* depth of a FIFO is *not necessarily* consistent with the *depth* selected in the GUI, because the actual depth of the FIFO depends on its implementation and the features that influence its implementation. In the FIFO Generator GUI, the actual depth of the FIFO is reported: the following section provides formulas or calculations used to report this information.

Block RAM, Distributed RAM and Shift RAM FIFOs

The actual FIFO depths for the block RAM, Distributed RAM and Shift RAM FIFOs are influenced by the following features that change its implementation:

- Common or Independent Clock
- Standard or FWFT Read Mode
- Symmetric or Non-symmetric Port Aspect Ratio

Depending on how a FIFO is configured, the calculation for the actual FIFO depth varies.

- Common Clock FIFO in Standard Read Mode
 $actual_write_depth = gui_write_depth$
 $actual_read_depth = gui_read_depth$
- Common Clock FIFO in FWFT Read Mode
 $actual_write_depth = gui_write_depth + 2$
 $actual_read_depth = gui_read_depth + 2$
- Independent Clock FIFO in Standard Read Mode
 $actual_write_depth = gui_write_depth - 1$
 $actual_read_depth = gui_read_depth - 1$
- Independent Clock FIFO in FWFT Read Mode
 $actual_write_depth = (gui_write_depth - 1) + (2 * round_down(gui_write_depth / gui_read_depth))$
 $actual_read_depth = gui_read_depth + 1$

Notes

1. Gui_write_depth = actual write (input) depth selected in the GUI
2. Gui_read_depth = actual read (output) depth selected in the GUI
3. Non-symmetric port aspect ratio feature (gui_write_depth not equal to gui_read_depth) is only supported in block RAM based FIFOs.

Virtex-5 FPGA Built-In FIFOs

The actual FIFO depths for the Virtex-5 FPGA Built-in FIFOs are influenced by the following features, which change its implementation:

- Common or Independent Clock
- Standard or FWFT Read Mode
- Built-In FIFO primitive used in implementation (minimum depth is 512)

Depending on how a FIFO is configured, the calculation for the actual FIFO depth varies.

- Independent Clock FIFO in Standard Read Mode
 $actual_write_depth = (primitive_depth + 2) * (N - 1) + (primitive_depth + 1)$
- Independent Clock FIFO in FWFT Read Mode
 $actual_write_depth = (primitive_depth + 2) * N$
- Common Clock FIFO in Standard Read Mode
 $actual_write_depth = (primitive_depth + 1) * (N - 1) + primitive_depth$
- Common Clock FIFO in FWFT Read Mode
 $actual_write_depth = (primitive_depth + 1) * N$

Notes

1. primitive_depth = depth of the primitive used to implement the FIFO; this information is reported in the GUI
2. N = number of primitive cascaded in depth or roundup (gui_write_depth / primitive_depth)

Virtex-4 FPGA Built-In FIFOs

The actual FIFO depths for the Virtex-4 FPGA Built-in FIFOs are influenced by the following features, which change its implementation:

- Read and Write Clock Frequencies
- Built-In FIFO primitive used in implementation (minimum depth is 512)

Depending on how a FIFO is configured, the calculation for the actual FIFO depth varies.

- Common/Independent Clock FIFO in Standard Read Mode and RD_CLK frequency > WR_CLK frequency

$$\text{actual_write_depth} = \text{primitive_depth} + 12$$

- Common/Independent Clock FIFO in Standard Read Mode and RD_CLK frequency <= WR_CLK frequency

$$\text{actual_write_depth} = \text{primitive_depth} + 15$$

Note: primitive_depth = depth of the primitive used to implement the FIFO.

Latency

This section defines the latency in which different output signals of the FIFO are updated in response to read or write operations.

Note: Latency is defined as the number of clock edges after a read or write operation occur before the signal is updated. Example: if latency is 0, that means that the signal is updated at the clock edge in which the operation occurred.

Non-Built-in FIFOs: Common Clock and Standard Read Mode Implementations

Table 4-10 defines the write port flags update latency due to a write operation for non-Built-in FIFOs such as block RAM, Distributed RAM, and Shift RAM FIFOs.

Table 4-10: Write Port Flags Update Latency Due to Write Operation

Signals	Latency (CLK)
FULL	0
ALMOST_FULL	0
PROG_FULL	1
WR_ACK	0
OVERFLOW	0

Table 4-11 defines the read port flags update latency due to a read operation.

Table 4-11: Read Port Flags Update Latency Due to Read Operation

Signals	Latency (CLK)
EMPTY	0
ALMOST_EMPTY	0

Table 4-11: Read Port Flags Update Latency Due to Read Operation

PROG_EMPTY	1
VALID	0
UNDERFLOW	0
DATA_COUNT	0

Table 4-12 defines the write port flags update latency due to a read operation. Table 4-13

Table 4-12: Write Port Flags Update Latency Due to Read Operation

Signals	Latency (CLK)
FULL	0
ALMOST_FULL	0
PROG_FULL	1
WR_ACK ¹	N/A
OVERFLOW ¹	N/A

1. Write handshaking signals are only impacted by a write operation.

Table 4-13 defines the read port flags update latency due to a write operation.

Table 4-13: Read Port Flags Update Latency Due to Write Operation

Signals	Latency (CLK)
EMPTY	0
ALMOST_EMPTY	0
PROG_EMPTY	1
VALID ¹	N/A
UNDERFLOW ¹	N/A
DATA_COUNT	0

1. Read handshaking signals are only impacted by a read operation.

Non-Built-in FIFOs: Common CLock and FWFT Read Mode Implementations

Table 4-14 defines the write port flags update latency due to a write operation for non-Built-in FIFOs such as block RAM, Distributed RAM, and Shift RAM FIFOs.

Table 4-14: Write Port Flags Update Latency due to Write Operation

Signals	Latency (CLK)
FULL	0
ALMOST_FULL	0
PROG_FULL	1

Table 4-14: Write Port Flags Update Latency due to Write Operation

WR_ACK	0
OVERFLOW	0

Table 4-15 defines the read port flags update latency due to a read operation.

Table 4-15: Read Port Flags Update Latency due to Read Operation

Signals	Latency (CLK)
EMPTY	0
ALMOST_EMPTY	0
PROG_EMPTY	1
VALID	0
UNDERFLOW	0
DATA_COUNT	0

Table 4-16 defines the write port flags update latency due to a read operation.

Table 4-16: Write Port Flags Update Latency Due to Read Operation

Signals	Latency (CLK)
FULL	0
ALMOST_FULL	0
PROG_FULL	1
WR_ACK ¹	N/A
OVERFLOW ¹	N/A

1. Write handshaking signals are only impacted by a write operation.

Table 4-17 defines the read port flags update latency due to a write operation.

Table 4-17: Read Port Flags Update Latency Due to Write Operation

Signals	Latency (CLK)
EMPTY	2
ALMOST_EMPTY	1
PROG_EMPTY	1
VALID ¹	N/A
UNDERFLOW ¹	N/A
DATA_COUNT	0

1. Read handshaking signals are only impacted by a read operation.

Non-Built-in FIFOs: Independent Clock and Standard Read Mode Implementations

Table 4-18 defines the write port flags update latency due to a write operation.

Table 4-18: Write Port Flags Update Latency Due to a Write Operation

Signals	Latency (WR_CLK)
FULL	0
ALMOST_FULL	0
PROG_FULL	1
WR_ACK	0
OVERFLOW	0
WR_DATA_COUNT	1

Table 4-19 defines the read port flags update latency due to a read operation.

Table 4-19: Read Port Flags Update Latency Due to a Read Operation

Signals	Latency (RD_CLK)
EMPTY	0
ALMOST_EMPTY	0
PROG_EMPTY	1
VALID	0
UNDERFLOW	0
RD_DATA_COUNT	1

Table 4-20 defines the write port flags update latency due to a read operation.

Table 4-20: Write Port Flags Update Latency Due to a Read Operation

Signals	Latency
FULL	$1 \text{ RD_CLK} + 4 \text{ WR_CLK} (+1 \text{ WR_CLK})^1$
ALMOST_FULL	$1 \text{ RD_CLK} + 4 \text{ WR_CLK} (+1 \text{ WR_CLK})^1$
PROG_FULL	$1 \text{ RD_CLK} + 5 \text{ WR_CLK} (+1 \text{ WR_CLK})^1$
WR_ACK ²	N/A
OVERFLOW ²	N/A
WR_DATA_COUNT	$1 \text{ RD_CLK} + 4 \text{ WR_CLK} (+1 \text{ WR_CLK})^1$

1. The crossing clock domain logic in independent clock FIFOs introduces a 1 WR_CLK uncertainty to the latency calculation.
2. Write handshaking signals are only impacted by a write operation.

Table 4-21 defines the read port flags update latency due to a write operation.

Table 4-21: Read Port Flags Update Latency Due to a Write Operation

Signals	Latency
EMPTY	$1 \text{ WR_CLK} + 4 \text{ RD_CLK} (+1 \text{ RD_CLK})^1$
ALMOST_EMPTY	$1 \text{ WR_CLK} + 4 \text{ RD_CLK} (+1 \text{ RD_CLK})^1$
PROG_EMPTY	$1 \text{ WR_CLK} + 5 \text{ RD_CLK} (+1 \text{ RD_CLK})^1$
VALID ²	N/A
UNDERFLOW ²	N/A
RD_DATA_COUNT	$1 \text{ WR_CLK} + 4 \text{ RD_CLK} (+1 \text{ RD_CLK})^1$

Note: Read handshaking signals only impacted by read operation.

1. The crossing clock domain logic in independent clock FIFOs introduces a 1 RD_CLK uncertainty to the latency calculation.
2. Read handshaking signals are only impacted by a read operation.

Non-Built-in FIFOs: Independent Clock and FWFT Read Mode Implementations

Table 4-22 defines the write port flags update latency due to a write operation.

Table 4-22: Write Port Flags Update Latency Due to a Write Operation

Signals	Latency (WR_CLK)
FULL	0
ALMOST_FULL	0
PROG_FULL	1
WR_ACK	0
OVERFLOW	0
WR_DATA_COUNT	1

Table 4-23 defines the read port flags update latency due to a read operation.

Table 4-23: Read Port Flags Update Latency Due to a Read Operation

Signals	Latency (RD_CLK)
EMPTY	0
ALMOST_EMPTY	0
PROG_EMPTY	1
VALID	0
UNDERFLOW	0
RD_DATA_COUNT	1

Table 4-24 defines the write port flags update latency due to a read operation.

Table 4-24: Write Port Flags Update Latency Due to a Read Operation

Signals	Latency
FULL	$1 \text{ RD_CLK} + 4 \text{ WR_CLK} (+1 \text{ WR_CLK})^1$
ALMOST_FULL	$1 \text{ RD_CLK} + 4 \text{ WR_CLK} (+1 \text{ WR_CLK})^1$
PROG_FULL	$1 \text{ RD_CLK} + 5 \text{ WR_CLK} (+1 \text{ WR_CLK})^1$
WR_ACK ²	N/A
OVERFLOW ²	N/A
WR_DATA_COUNT	$1 \text{ RD_CLK} + 4 \text{ WR_CLK} (+1 \text{ WR_CLK})^1$

1. The crossing clock domain logic in independent clock FIFOs introduces a 1 WR_CLK uncertainty to the latency calculation.
2. Write handshaking signals are only impacted by a write operation.

Table 4-25 defines the read port flags update latency due to a write operation.

Table 4-25: Read Port Flags Update Latency Due to a Write Operation

Signals	Latency
EMPTY	$1 \text{ WR_CLK} + 6 \text{ RD_CLK} (+1 \text{ RD_CLK})^1$
ALMOST_EMPTY	$1 \text{ WR_CLK} + 6 \text{ RD_CLK} (+1 \text{ RD_CLK})^1$
PROG_EMPTY	$1 \text{ WR_CLK} + 5 \text{ RD_CLK} (+1 \text{ RD_CLK})^1$
VALID ²	N/A
UNDERFLOW ²	N/A
RD_DATA_COUNT	$1 \text{ WR_CLK} + 4 \text{ RD_CLK} (+1 \text{ RD_CLK})^1 + [2 \text{ RD_CLK} (+1 \text{ RD_CLK})]^3$

Note: Read handshaking signals only impacted by read operation.

1. The crossing clock domain logic in independent clock FIFOs introduces a 1 RD_CLK uncertainty to the latency calculation.
2. Read handshaking signals are only impacted by a read operation.
3. This latency is the worst-case latency. The addition of the $[2 \text{ RD_CLK} (+1 \text{ RD_CLK})]$ latency depends on the status of the EMPTY and ALMOST_EMPTY flags.

Virtex-5 FPGA Built-in FIFOs: Common Clock and Standard Read Mode Implementations

Note: N is the number of primitives cascaded in depth; this can be calculated by dividing the GUI depth by the primitive depth.

Table 4-26 defines the write port flags update latency due to a write operation.

Table 4-26: Write Port Flags Update Latency Due to Write Operation

Signals	Latency (CLK)
FULL	0
PROG_FULL	1
WR_ACK	0
OVERFLOW	0

Table 4-27 defines the read port flags update latency due to a read operation.

Table 4-27: Read Port Flags Update Latency Due to Read Operation

Signals	Latency (CLK)
EMPTY	0
PROG_EMPTY	1
VALID	0
UNDERFLOW	0

Table 4-28 defines the write port flags update latency due to a read operation.

Table 4-28: Write Port Flags Update Latency Due to Read Operation

Signals	Latency (CLK)
FULL	(N-1)
PROG_FULL	N
WR_ACK ¹	N/A
OVERFLOW ¹	N/A

1. Write handshaking signals are only impacted by a write operation.

Table 4-29 defines the read port flags update latency due to a write operation.

Table 4-29: Read Port Flags Update Latency Due to Write Operation

Signals	Latency (CLK)
EMPTY	$(N-1)*2$
PROG_EMPTY	$(N-1)*2+1$
VALID ¹	N/A
UNDERFLOW ¹	N/A

Note: Read handshaking signals only impacted by read operation.

1. Read handshaking signals are only impacted by a read operation.

Virtex-5 FPGA Built-in FIFOs: Common Clock and FWFT Read Mode Implementations

Note: N is the number of primitives cascaded in depth; this can be calculated by dividing the GUI depth by the primitive depth.

Table 4-30 defines the write port flags update latency due to a write operation.

Table 4-30: Write Port Flags Update Latency Due to Write Operation

Signals	Latency (CLK)
FULL	0
PROG_FULL	1
WR_ACK	0
OVERFLOW	0

Table 4-31 defines the read port flags update latency due to a read operation.

Table 4-31: Read Port Flags Update Latency Due to a Read Operation

Signals	Latency (CLK)
EMPTY	0
PROG_EMPTY	1
VALID	0
UNDERFLOW	0

Table 4-32 defines the write port flags update latency due to a read operation.

Table 4-32: Write Port Flags Update Latency Due to a Read Operation

Signals	Latency (CLK)
FULL	$(N-1)$
PROG_FULL ¹	N

Table 4-32: Write Port Flags Update Latency Due to a Read Operation

WR_ACK ¹	N/A
OVERFLOW	N/A

1. Write handshaking signals are only impacted by a write operation.

Table 4-33 defines the read port flags update latency due to a write operation

Table 4-33: Read Port Flags Update Latency Due to a Write Operation

Signals	Latency (CLK)
EMPTY	$((N-1)*2+1)$
PROG_EMPTY	$((N-1)*2+1)$
VALID ¹	N/A
UNDERFLOW ¹	N/A

1. Read handshaking signals are only impacted by a read operation.

Virtex-5 FPGA Built-in FIFOs: Independent Clocks and Standard Read Mode Implementations

Note: N is the number of primitives cascaded in depth; this can be calculated by dividing the GUI depth by the primitive depth. *Faster_Clk* is the clock domain, either RD_CLK or WR_CLK, that has a larger frequency.

Table 4-34 defines the write port flags update latency due to a write operation.

Table 4-34: Write Port Flags Update Latency Due to a Write Operation

Signals	Latency (WR_CLK)
FULL	0
PROG_FULL	1
WR_ACK	0
OVERFLOW	0

Table 4-35 defines the read port flags update latency due to a read operation.

Table 4-35: Read Port Flags Update Latency Due to a Read Operation

Signals	Latency (RD_CLK)
EMPTY	0
PROG_EMPTY	1
VALID	0
UNDERFLOW	0

Table 4-36 defines the write port flags update latency due to a read operation.

Table 4-36: Write Port Flags Update Latency Due to a Read Operation

Signals	Latency
FULL	$(N-1)*5 \text{ faster_clk} + 4 \text{ WR_CLK}$
PROG_FULL	$(N-1)*4 \text{ faster_clk} + 3 \text{ WR_CLK}$
WR_ACK ¹	N/A
OVERFLOW ¹	N/A

1. Write handshaking signals are only impacted by a write operation.

Table 4-37 defines the read port flags update latency due to a write operation.

Table 4-37: Read Port Flags Update Latency Due to a Write Operation

Signals	Latency
EMPTY	$(N-1)*4 \text{ faster_clk} + 3 \text{ RD_CLK}$
PROG_EMPTY	$(N-1)*4 \text{ faster_clk} + 3 \text{ RD_CLK}$
VALID ¹	N/A
UNDERFLOW ¹	N/A

1. Read handshaking signals are only impacted by a read operation.

Virtex-5 FPGA Built-in FIFOs: Independent Clocks and FWFT Read Mode Implementations

Note: N is the number of primitives cascaded in depth, which can be calculated by dividing the GUI depth by the primitive depth. *Faster_Clk* is the clock domain, either RD_CLK or WR_CLK, that has a larger frequency.

Table 4-38 defines the write port flags update latency due to a write operation.

Table 4-38: Write Port Flags Update Latency Due to a Write Operations

Signals	Latency (WR_CLK)
FULL	0
PROG_FULL	1

Table 4-38: Write Port Flags Update Latency Due to a Write Operations (Continued)

WR_ACK	0
OVERFLOW	0

Table 4-39 defines the read port flags update latency due to a read operation.

Table 4-39: Read Port Flags Update Latency Due to a Read Operation

Signals	Latency (RD_CLK)
EMPTY	0
PROG_EMPTY	1
VALID	0
UNDERFLOW	0

Table 4-40 defines the write port flags update latency due to a read operation.

Table 4-40: Write Port Flags Update Latency Due to a Read Operation

Signals	Latency
FULL	$(N-1)*5 \text{ faster_clk} + 4 \text{ WR_CLK}$
PROG_FULL	$(N-1)*4 \text{ faster_clk} + 3 \text{ WR_CLK}$
WR_ACK ¹	N/A
OVERFLOW ¹	N/A

1. Write handshaking signals are only impacted by a write operation.

Table 4-41 defines the read port flags update latency due to a write operation.

Table 4-41: Read Port Flags Update Latency Due to a Write Operation

Signals	Latency
EMPTY	$(N-1)*5 \text{ faster_clk} + 4 \text{ RD_CLK}$
PROG_EMPTY	$(N-1)*4 \text{ faster_clk} + 3 \text{ RD_CLK}$
VALID ¹	N/A
UNDERFLOW ¹	N/A

1. Read handshaking signals are only impacted by a read operation.

Special Design Considerations

This chapter provides additional design considerations for using the FIFO Generator core.

Resetting the FIFO

The FIFO Generator must be reset after the FPGA is configured and before operation begins. Two reset pins are available, asynchronous (RST) and synchronous (SRST), and both clear the internal counters and output registers.

- For asynchronous reset, internal to the core, RST is synchronized to the clock domain in which it is used, to ensure that the FIFO initializes to a known state. This synchronization logic allows for proper reset timing of the core logic, avoiding glitches and metastable behavior.
- For synchronous reset, because the reset pin is synchronous to the input clock and there is only one clock domain in the FIFO, no additional synchronization logic is needed.

The generated FIFO core will be initialized after reset to a known state. For details about reset values and behavior, see “Reset Behavior” in Chapter 4 of this guide.

Continuous Clocks

The FIFO Generator is designed to work only with free-running write and read clocks. Xilinx does not recommend controlling the core by manipulating RD_CLK and WR_CLK. If this functionality is required to gate FIFO operation, we recommend using the write enable (WR_EN) and read enable (RD_EN) signals.

Pessimistic Full and Empty

When independent clock domains are selected, the full flag (FULL, ALMOST_FULL) and empty flag (EMPTY, ALMOST_EMPTY) are pessimistic flags. FULL and ALMOST_FULL are synchronous to the write clock (WR_CLK) domain, while EMPTY and ALMOST_EMPTY are synchronous to the read clock (RD_CLK) domain.

The full flags are considered pessimistic flags because they assume that no read operations have taken place in the read clock domain. ALMOST_FULL is guaranteed to be asserted on the rising edge of WR_CLK when there is only one available location in the FIFO, and FULL is guaranteed to be asserted on the rising edge of WR_CLK when the FIFO is full. There may be a number of clock cycles between a read operation and the deassertion of FULL. The precise number of clock cycles for FULL to deassert is not predictable due to the crossing of clock domains and synchronization logic. For more information see “Simultaneous Assertion of Full and Empty Flag.”

The EMPTY flags are considered pessimistic flags because they assume that no write operations have taken place in the write clock domain. ALMOST_EMPTY is guaranteed to be asserted on the rising edge of RD_CLK when there is only one more word in the FIFO, and EMPTY is guaranteed to be asserted on the rising edge of RD_CLK when the FIFO is empty. There may be a number of clock cycles between a write operation and the deassertion of EMPTY. The precise number of clock cycles for EMPTY to deassert is not predictable due to the crossing of clock domains and synchronization logic. For more information see [“Simultaneous Assertion of Full and Empty Flag.”](#)

See [Chapter 4, “Designing with the Core,”](#) for detailed information about the latency and behavior of the full and empty flags.

Programmable Full and Empty

The programmable full (PROG_FULL) and programmable empty (PROG_EMPTY) flags provide the user flexibility in specifying when the programmable flags assert and deassert. These flags can be set either by constant value(s) or by input port(s). These signals differ from the full and empty flags because they assert one (or more) clock cycle *after* the assert threshold has been reached. These signals are deasserted some time after the negate threshold has been passed. In this way, PROG_EMPTY and PROG_FULL are also considered pessimistic flags. See [“Programmable Flags”](#) in [Chapter 4](#) of this guide for more information about the latency and behavior of the programmable flags.

Simultaneous Assertion of Full and Empty Flag

For independent clock FIFO, there are delays in the assertion/deassertion of the full and empty flags due to cross clock domain logic. These delays may cause unexpected FIFO behavior like full and empty asserting at the same time. To avoid this, the following A and B equations must be true.

A) Time it takes to update full flag due to read operation < time it takes to empty a full FIFO

B) Time it takes to update empty flag due to write operation < time it takes to fill an empty FIFO

For example, assume the following configurations:

Independent clock (non built-in), standard FIFO

write clock frequency = 3MHz, wr_clk_period = 333 ns

read clock frequency = 148 MHz, rd_clk_period = 6.75 ns

write depth = read depth = 20

actual_wr_depth = actual_rd_depth = 19 (as mentioned in [“Actual FIFO Depth”](#) in [Chapter 4](#))

Apply equation A:

Time it takes to update full flag due to read operation < time it takes to empty a full FIFO
 $= 1 * rd_clk_period + 5 * wr_clk_period < actual_rd_depth * rd_clk_period$

$1 * 6.75 + 5 * 333 < 19 * 6.75$

$1671.75 \text{ ns} < 128.5 \text{ ns} \rightarrow$ Equation VIOLATED!

Note: Left side equation is the latency of full flag updating due to read operation as mentioned in [Table 4-20](#).

Conclusion: Violation of this equation proves that for this design, when a FULL FIFO is read from continuously, the empty flag asserts before the full flag deasserts due to the read operations that occurred.

Apply Equation B:

Time it takes to update empty flag due to write operation < time it takes to fill an empty FIFO

$$1 * \text{wr_clk_period} + 5 * \text{rd_clk_period} < \text{actual_wr_depth} * \text{wr_clk_period}$$

$$1 * 333 + 5 * 6.75 < 19 * 333$$

$$366.75 \text{ ns} < 6327 \text{ ns} \rightarrow \text{Equation MET!}$$

Note: Left side equation is the latency of empty flag updating due to write operation as mentioned in [Table 4-21](#).

Conclusion: Because this equation is met for this design, an EMPTY FIFO that is written into continuously has its empty flag deassert before the full flag is asserted.

Write Data Count and Read Data Count

When independent clock domains are selected, write data count (WR_DATA_COUNT) and read data count (RD_DATA_COUNT) signals are provided as an indication of the number of words in the FIFO relative to the write or read clock domains, respectively.

Consider the following when using the WR_DATA_COUNT or RD_DATA_COUNT ports.

- The WR_DATA_COUNT and RD_DATA_COUNT outputs are not an instantaneous representation of the number of words in the FIFO, but can instantaneously provide an approximation of the number of words in the FIFO.
- WR_DATA_COUNT and RD_DATA_COUNT may skip values from clock cycle to clock cycle.
- Using non-symmetric aspect ratios, or running clocks which vary dramatically in frequency, will increase the disparity between the data count outputs and the actual number of words in the FIFO.

Note: The WR_DATA_COUNT and RD_DATA_COUNT outputs will always be correct after some period of time where RD_EN=0 and WR_EN=0 (generally, just a few clock cycles after read and write activity stops).

See “Data Counts” in [Chapter 4](#) of this guide for details about the latency and behavior of the data count flags.

Setup and Hold Time Violations

When generating a FIFO with independent clock domains, the core internally synchronizes the write and read clock domains. For this reason, setup and hold time violations are expected on certain registers within the core. In simulation, warning messages may be issued indicating these violations. If these warning messages are from the FIFO Generator core, they can be safely ignored. The core is designed to properly handle these conditions, regardless of the phase or frequency relationship between the write and read clocks.

Alternatively, there are two ways to disable these expected setup and hold time violations due to data synchronization between clock domains:

- Add the following constraint to your design—this constraint sets a timing constraint to the synchronization logic by requiring a maximum set of delays. The maximum delays used is defined by 2x of the slower clock period.

```
NET fifoinstance/grf.rf/gcx.clkx/wr_pntr_gc<0> MAXDELAY = 12 ns;  
NET fifoinstance/grf.rf/gcx.clkx/wr_pntr_gc<1> MAXDELAY = 12 ns;  
...  
NET fifoinstance/grf.rf/gcx.clkx/wr_pntr_gc<9> MAXDELAY = 12 ns;  
  
NET fifoinstance/grf.rf/gcx.clkx/rd_pntr_gc<0> MAXDELAY = 12 ns;  
NET fifoinstance/grf.rf/gcx.clkx/rd_pntr_gc<1> MAXDELAY = 12 ns;  
...  
NET fifoinstance/grf.rf/gcx.clkx/rd_pntr_gc<9> MAXDELAY = 12 ns;
```

- Add the following constraint to your design—this constraint directs the tool to ignore the appropriate paths that are part of the synchronization logic:

```
NET fifoinstance/grf.rf/gcx.clkx/wr_pntr_gc<0> TIG;  
NET fifoinstance/grf.rf/gcx.clkx/wr_pntr_gc<1> TIG;  
...  
NET fifoinstance/grf.rf/gcx.clkx/wr_pntr_gc<9> TIG;  
  
NET fifoinstance/grf.rf/gcx.clkx/rd_pntr_gc<0> TIG;  
NET fifoinstance/grf.rf/gcx.clkx/rd_pntr_gc<1> TIG;  
...  
NET fifoinstance/grf.rf/gcx.clkx/rd_pntr_gc<9> TIG;
```

Simulating Your Design

The FIFO Generator is provided as a Xilinx technology-specific netlist, and as a behavioral or structural simulation model. This chapter provides instructions for simulating the FIFO Generator in your design.

Simulation Models

The FIFO Generator supports two types of simulation models based on the Xilinx CORE Generator system project options. The models are available in both VHDL and Verilog®. Both types of models are described in detail in this chapter.

To choose a model:

1. Open the CORE Generator.
2. Select Options from the Project drop-down list.
3. Click the Generation tab.
4. Choose to generate a behavioral model or a structural model.

Behavioral Models

Important! The behavioral models provided are designed to reproduce the behavior and functionality of the FIFO Generator, but are not cycle-accurate models (except for the common clock FIFO with block RAM, distributed RAM, or shift registers). If cycle accurate models are required (and common clock FIFO with block RAM, distributed RAM or shift registers is not selected), it is recommended to use the structural model.

The behavioral models are considered to be zero-delay models, as the modeled write-to-read latency is nearly zero. The behavioral models are functionally correct, and will represent the behavior of the configured FIFO, although the write-to-read latency and the behavior of the status flags will differ from the actual implementation of the FIFO design.

To generate behavioral models, select Behavioral and VHDL or Verilog in the Xilinx CORE Generator project options. Behavioral models are the default project options.

The following considerations apply to the behavioral models.

- Write operations always occur relative to the write clock (WR_CLK) or common clock (CLK) domain, as do the corresponding handshaking signals.
- Read operations always occur relative to the read clock (RD_CLK) or common clock (CLK) domain, as do the corresponding handshaking signals.
- The delay through the FIFO (write-to-read latency) will differ between the VHDL model, the Verilog model, and the core.
- The deassertion of the status flags (full, almost full, programmable full, empty, almost

empty, programmable empty) will vary between the VHDL model, the Verilog model, and the core.

Note: If independent clocks or common clocks with built-in FIFO is selected, the user must use the structural model, as the behavioral model does not correctly model the behavior of the status flags (full, programmable full, empty and programmable empty).

Structural Models

The structural models are designed to provide a more accurate model of FIFO behavior at the cost of simulation time. These models will provide a closer approximation of cycle accuracy across clock domains for asynchronous FIFOs. No asynchronous FIFO model can be 100% cycle accurate as physical relationships between the clock domains, including temperature, process, and frequency relationships, affect the domain crossing indeterminately.

To generate structural models, select Structural and VHDL or Verilog in the Xilinx CORE Generator project options.

Note: Simulation performance may be impacted when simulating the structural models compared to the behavioral models

Performance Information

Resource Utilization and Performance

Performance and resource utilization for a FIFO varies depending on the configuration and features selected during core customization. The following tables show resource utilization data and maximum performance values for a variety of sample FIFO configurations.

[Table A-1](#) provides results for a FIFO configured without optional features. The benchmarks were performed using Virtex-II 2v3000, Virtex-4 4vlx15 -11, and Virtex-5 5vlx50-2 FPGAs.

Table A-1: Benchmarks: FIFO Configured without Optional Features

FIFO Type	Depth x Width	FPGA Family	Performance (MHz)	Resources				
				LUTs	FFs	Block RAM	Shift Register	Distributed RAM
Synchronous FIFO (block RAM)	512 x 16	Virtex-5	345 MHz	40	40	1	0	0
		Virtex-4	285 MHz	23	40	1	0	0
		Virtex-II	195 MHz	23	40	1	0	0
Synchronous FIFO (block RAM)	4096 x 16	Virtex-5	345 MHz	50	52	2	0	0
		Virtex-4	285 MHz	26	52	4	0	0
		Virtex-II	190 MHz	26	52	4	0	0
Synchronous FIFO (Distributed RAM)	64 x 16	Virtex-5	470 MHz	25	44	0	0	22
		Virtex-4	385 MHz	29	28	0	0	128
		Virtex-II	265 MHz	29	67	0	0	128
Synchronous FIFO (Distributed RAM)	512 x 16	Virtex-5	320 MHz	60	56	0	0	256
		Virtex-4	255 MHz	313	196	0	0	1024
		Virtex-II	185 MHz	97	218	0	0	1024
Independent Clocks FIFO (block RAM)	512x 16	Virtex-5	370 MHz	72	193	1	0	0
		Virtex-4	365 MHz	62	121	1	0	0
		Virtex-II	230 MHz	58	121	1	0	0

Table A-1: Benchmarks: FIFO Configured without Optional Features (Continued)

FIFO Type	Depth x Width	FPGA Family	Performance (MHz)	Resources				
				LUTs	FFs	Block RAM	Shift Register	Distributed RAM
Independent Clocks FIFO (block RAM)	4096 x 16	Virtex-5	365 MHz	105	160	2	0	0
		Virtex-4	365 MHz	93	160	4	0	0
		Virtex-II	225 MHz	85	160	4	0	0
Independent Clocks FIFO (Distributed RAM)	64 x 16	Virtex-5	465 MHz	44	98	0	0	22
		Virtex-4	405 MHz	90	100	0	0	128
		Virtex-II	290 MHz	52	103	0	0	128
Independent Clocks FIFO (Distributed RAM)	512 x 16	Virtex-5	355 MHz	92	137	0	0	256
		Virtex-4	270 MHz	350	269	0	0	1024
		Virtex-II	195 MHz	130	291	0	0	1024
Shift Register FIFO	64 x 16	Virtex-5	420 MHz	56	43	0	32	0
		Virtex-4	370 MHz	56	43	0	64	0
		Virtex-II	255 MHz	80	43	0	64	0
Shift Register FIFO	512 x 16	Virtex-5	300 MHz	134	52	0	256	0
		Virtex-4	245 MHz	315	56	0	512	0
		Virtex-II	180 MHz	304	56	0	512	0

Table A-2 provides results for FIFOs configured with multiple programmable thresholds. The benchmarks were performed using Virtex-II 2v3000, Virtex-4 4vlx15 -11, and Virtex-5 5vlx50-2 FPGAs.

Table A-2: Benchmarks: FIFO Configured with Multiple Programmable Thresholds

FIFO Type	Depth x Width	FPGA Family	Performance (MHz)	Resources				
				LUTs	FFs	Block RAM	Shift Register	Distributed RAM
Synchronous FIFO (block RAM)	512 x 16	Virtex-5	325 MHz	73	69	1	0	0
		Virtex-4	275 MHz	59	69	1	0	0
		Virtex-II	195 MHz	61	69	1	0	0
Synchronous FIFO (block RAM)	4096 x 16	Virtex-5	345 MHz	87	81	2	0	0
		Virtex-4	285 MHz	71	81	4	0	0
		Virtex-II	190 MHz	73	81	4	0	0
Synchronous FIFO (Distributed RAM)	64 x 16	Virtex-5	450 MHz	45	61	0	0	22
		Virtex-4	385 MHz	92	79	0	0	128
		Virtex-II	235 MHz	55	88	0	0	128

Table A-2: Benchmarks: FIFO Configured with Multiple Programmable Thresholds (Continued)

FIFO Type	Depth x Width	FPGA Family	Performance (MHz)	Resources				
				LUTs	FFs	Block RAM	Shift Register	Distributed RAM
Synchronous FIFO (Distributed RAM)	512 x 16	Virtex-5	330 MHz	86	79	0	0	256
		Virtex-4	250 MHz	349	215	0	0	1024
		Virtex-II	190 MHz	132	245	0	0	1024
Independent Clocks FIFO (block RAM)	512x 16	Virtex-5	375 MHz	100	142	1	0	0
		Virtex-4	360 MHz	89	142	1	0	0
		Virtex-II	230 MHz	92	142	1	0	0
Independent Clocks FIFO (block RAM)	4096 x 16	Virtex-5	385 MHz	142	187	2	0	0
		Virtex-4	365 MHz	131	187	4	0	0
		Virtex-II	215 MHz	130	187	4	0	0
Independent Clocks FIFO (Distributed RAM)	64 x 16	Virtex-5	465 MHz	82	113	0	0	22
		Virtex-4	405 MHz	114	115	0	0	128
		Virtex-II	245 MHz	75	115	0	0	128
Independent Clocks FIFO (Distributed RAM)	512 x 16	Virtex-5	365 MHz	120	158	0	0	256
		Virtex-4	270 MHz	385	290	0	0	1024
		Virtex-II	190 MHz	163	312	0	0	1024
Shift Register FIFO	64 x 16	Virtex-5	425 MHz	75	59	0	32	0
		Virtex-4	370 MHz	105	59	0	64	0
		Virtex-II	250 MHz	105	59	0	64	0
Shift Register FIFO	512 x 16	Virtex-5	305 MHz	160	74	0	256	0
		Virtex-4	255 MHz	354	78	0	512	0
		Virtex-II	180 MHz	343	78	0	512	0

Table A-3 provides results for FIFOs configured to use the Virtex-5 built-in FIFO. The benchmarks were performed using a Virtex-5 5v1x50-2 FPGA.

Table A-3: Benchmarks: FIFO Configured with Virtex-5 FIFO36 Resources

FIFO Type	Depth x Width	Read Mode	Performance (MHz)	Resources		
				LUTs	FFs	FIFO36s
Synchronous FIFO36 (basic)	512 x 72	Standard	350	0	2	1
		FWFT	355	2	4	1
	16k x 8	Standard	330	10	6	4
		FWFT	320	13	10	4

Table A-3: Benchmarks: FIFO Configured with Virtex-5 FIFO36 Resources

FIFO Type	Depth x Width	Read Mode	Performance (MHz)	Resources		
				LUTs	FFs	FIFO36s
Synchronous FIFO36 (with handshaking)	512 x 72	Standard	350	2	6	1
		FWFT	350	5	6	1
	16k x 8	Standard	325	12	12	4
		FWFT	325	16	13	4
Independent Clocks FIFO36 (basic)	512 x 72	Standard	500	0	2	1
		FWFT	500	0	2	1
	16k x 8	Standard	350	6	2	4
		FWFT	350	6	2	4
Independent Clocks FIFO36 (with handshaking)	512 x 72	Standard	500	2	6	1
		FWFT	450	2	3	1
	16k x 8	Standard	360	8	8	4
		FWFT	360	9	5	4

Table A-4 provides results for FIFOs configured to use the Virtex-4 FPGA built-in FIFO with patch. The benchmarks were performed using a Virtex-4 4vlx15 -11 FPGA.

Table A-4: Benchmarks: FIFO Configured with Virtex-4 FIFO16 Patch

FIFO Type	Depth x Width	Clock Ratios	Performance (MHz)	Resources			
				LUTs	FFs	Distributed RAMs	FIFO16s
Built-in FIFO (basic)	512 x 36	WR_CLK ≥ RD_CLK	375	110	129	72	1
		RD_CLK > WR_CLK	400	92	115	72	1
Built-in FIFO (with handshaking)	512 x 36	WR_CLK ≥ RD_CLK	375	113	134	72	1
		RD_CLK > WR_CLK	400	95	120	72	1

Core Parameters

FIFO Parameters

Table B-1 describes the FIFO core parameters, including the XCO file value and the default settings.

Table B-1: FIFO Parameter Table

Parameter Name	XCO File Values	Default GUI Setting
Component_Name	instance_name ASCII text starting with a letter and using the following character set: a-z, 0-9, and _	fifo_generator_v4_4
FIFO Implementation	Common_Clock_Block_RAM Common_Clock_Distributed_RAM Common_Clock_Shift_Register Common_Clock_Builtin_FIFO Independent_Clocks_Block_RAM Independent_Clocks_Distributed_RAM Independent_Clocks_Builtin_FIFO	Common_Clock_Block_RAM
Input Data Width ¹	Integer in range 1 to 1024	16
Output Data Width ¹	Integer in range 1 to 1024	16
Input Depth ¹	2 ^N where N is an integer 4 to 24	1024
Output Depth ¹	2 ^M where M is an integer 4 to 24	1024
Data Count Width	Integer in range 1 to log ₂ (Output Depth)	2
Read Clock Frequency	Integer 1 to 1000 (MHz)	1
Write Clock Frequency	Integer 1 to 1000 (MHz)	1
Almost Full Flag	true, false	false
Almost Empty Flag	true, false	false
Enable ECC	true, false	false
Programmable Full Type	No_Programmable_Full_Threshold Single_Programmable_Full_Threshold_Constant Multiple_Programmable_Full_Threshold_Constants Single_Programmable_Full_Threshold_Input_Port Multiple_Programmable_Full_Threshold_Input_Ports	No_Programmable_Full_Threshold
Full Threshold Assert Value	See range under Programmable Flags.	768
Full Threshold Negate Value	See range under "Programmable Flags," page 56.	768

Table B-1: FIFO Parameter Table (Continued)

Parameter Name	XCO File Values	Default GUI Setting
Programmable Empty Type	No_Programmable_Empty_Threshold Single_Programmable_Empty_Threshold_Constant Multiple_Programmable_Empty_Threshold_Constants Single_Programmable_Empty_Threshold_Input_Port Multiple_Programmable_Empty_Threshold_Input_Ports	No_Programmable_Empty_Threshold
Empty Threshold Assert Value	See range under “Programmable Flags,” page 56.	256
Empty Threshold Negate Value	See range under “Programmable Flags,” page 56.	256
Write Acknowledge Flag	true, false	false
Write Acknowledge Sense	Active_High, Active_Low	Active_High
Overflow Flag	true, false	false
Overflow Sense	Active_High, Active_Low	Active_High
Valid Flag	true, false	false
Valid Sense	Active_High, Active_Low	Active_High
Underflow Flag	true, false	false
Underflow Sense	Active_High, Active_Low	Active_High
Use Dout Reset	true, false	true
Dout Reset Value	Hex value in range of 0 to output data width - 1	0
Primitive Depth	512, 1024, 2048, 4096	1024
Read Data Count	true, false	false
Read Data Count Width	Integer in range 1 to $\log_2(\text{output depth})$	10
Write Data Count	true, false	false
Write Data Count Width	Integer in range 1 to $\log_2(\text{input depth})$	10
Data Count	true, false	false
Performance Options	First_Word_Fall_Through, Standard_Fifo	Standard_Fifo
Read Latency	integer range 0 to 1	1
Reset Pin	true, false	true
Use Embedded Registers	true, false	false
Full Flags Reset Value	1, 0	1

1. A user-customized core should not exceed the number of shift registers, built-in FIFOs, block RAM, or distributed RAM primitives available in the targeted architecture; it is the user’s responsibility to know the resource availability in the targeted device.